



Part Number . . .

FFA.OS.302.CLAC42

Size/Series OS / S

[Request a quote](#)

MECHANICAL DETAILS

Shell Style/Model FFA*: Straight plug, cable collet
Keying Hermaphroditic keying ("half moon" insert), plug has male pin 1
Housing Material Brass (chrome plated) shell and collet nut, nickel plated brass latch sleeve and mid pieces
Cable Fixing C42: 3.8 - 4.4 mm **NEW COLLET**
Variant :

	A	C	L	M	S2
mm.	9	4.2	34.5	24.5	6.5
in.	0.35	0.17	1.36	0.96	0.26

PERFORMANCE DETAILS



Insert Configuration OS.302 : 2 Low Voltage
Insulator L: PEEK
Vtest: 1500 V (AC), 2100 V (DC)
Rated Current: 10 A (AC/DC)

OTHER CHARACTERISTICS

Endurance (Shell) 3839 mating cycles
Humidity (max): <=95% [at 60 deg C /140 F]
Vibration: 15 g [10 Hz - 2000 Hz]
Shock Resistance: 100 g [6 ms]
Salt Spray Corrosion: >144 hr
Climatical Category: 50/175/21
Shielding (min): 75 dB (10 MHz)
Shielding (min): 40 dB (1 GHz)
IP Rating 50
[Catalog](#)



[Download 3D draw](#)



[Copyright](#) [Privacy policy](#) [Product safety](#)