



Part Number

FFA.1S.304.CLAC52Z

Size/Series 1S / S

[Request a quote](#)

MECHANICAL DETAILS

Shell Style/Model FFA*: Straight plug, cable collet and nut for fitting a bend relief


Keying Hermaphroditic keying ("half moon" insert), plug has male pin 1

Housing Material Brass (chrome plated) shell and collet nut, nickel plated brass latch sleeve and mid pieces

Cable Fixing C52: 4.3 - 5.1 mm

Variant Z : Nut for fitting a bend relief

	A	L	M	S2
mm.	12	42.5	31.5	9
in.	0.47	1.67	1.24	0.35



[Copyright](#) [Privacy policy](#) [Product safety](#)

PERFORMANCE DETAILS

Insert Configuration 1S.304 : 4 Low Voltage

Insulator L: PEEK

Vtest: 1200 V (AC), 1800 V (DC)

Rated Current: 10 A (AC/DC)

OTHER CHARACTERISTICS

Humidity (max): <=95% [at 60 deg C /140 F]

Vibration: 15 g [10 Hz - 2000 Hz]

Shock Resistance: 100 g [6 ms]

Salt Spray Corrosion: >144 hr

Climatical Category: 50/175/21

Shielding (min): 75 dB (10 MHz)

Shielding (min): 40 dB (1 GHz)

IP Rating 50

Catalog

