

MOS FET Relays


G3VM-355CR/FR

MOS FET Relay with Both SPST-NO and SPST-NC Contacts Incorporated in a Single DIP Package.

- SPST-NO/SPST-NC models included in the 350-V load series.
- Continuous load current of 120 mA.
- Dielectric strength of 2,500 Vrms between I/O.
- RoHS Compliant.

■ Application Examples

- Measurement devices
- Security systems
- Amusement machines



Note: The actual product is marked differently from the image shown here.


■ List of Models

Contact form	Terminals	Load voltage (peak value)	Model	Number per stick	Number per tape
SPST-NO/ SPST-NC	PCB terminals	350 VAC	G3VM-355CR	50	---
	Surface-mounting terminals		G3VM-355FR		
			G3VM-355FR(TR)	---	1,500


■ Dimensions

Note: All units are in millimeters unless otherwise indicated.

G3VM-355CR




Note: The actual product is marked differently from the image shown here.




Weight: 0.54 g

G3VM-355FR




Note: The actual product is marked differently from the image shown here.





■ Terminal Arrangement/Internal Connections (Top View)

G3VM-355CR




G3VM-355FR



The actual product is marked differently from the image shown here.


■ PCB Dimensions (Bottom View)

G3VM-355CR



■ Actual Mounting Pad Dimensions (Recommended Value, Top View)

G3VM-355FR



■ Absolute Maximum Ratings (Ta = 25°C)


Item		Symbol	Rating	Unit	Measurement conditions
Input	LED forward current	I _F	50	mA	
	Repetitive peak LED forward current	I _{FP}	1	A	100 μs pulses, 100 pps
	LED forward current reduction rate	Δ I _F /°C	– 0.5	mA/°C	Ta ≥ 25°C
	LED reverse voltage	V _R	5	V	
	Connection temperature	T _j	125	°C	
Output	Load voltage (AC peak/DC)	V _{OFF}	350	V	
	Continuous load current (AC peak/DC)	I _O	120	mA	
	ON current reduction rate	Δ I _{ON} /°C	– 1.2	mA/°C	Ta ≥ 25°C
	Connection temperature	T _j	125	°C	
Dielectric strength between input and output (See note 1.)		V _{I-O}	2,500	V _{rms}	AC for 1 min
Operating temperature		T _a	– 40 to +85	°C	With no icing or condensation
Storage temperature		T _{stg}	– 55 to +125	°C	With no icing or condensation
Soldering temperature (10 s)		---	260	°C	10 s

Note: 1. The dielectric strength between the input and output was checked by applying voltage between all pins as a group on the LED side and all pins as a group on the light-receiving side.

■ Electrical Characteristics (Ta = 25°C)

Item	Symbol	Minimum	Typical	Maximum	Unit	Measurement conditions
Input	LED forward voltage	V_F	1.0	1.15	1.3	V
	Reverse current	I_R	---	---	10	μA
	Capacity between terminals	C_T	---	30	---	pF
	Trigger LED forward current	I_{FT}	---	1	3	mA
Output	Maximum resistance with output ON	R_{ON}	15	25	Ω	SPST-NO: $I_O = 120 \text{ mA}$
						SPST-NC: $I_{OFF} = 10 \mu\text{A}$
						SPST-NO: $I_F = 5 \text{ mA}$, $I_O = 120 \text{ mA}$
						SPST-NC: $I_F = 0 \text{ mA}$, $I_O = 120 \text{ mA}$
	Current leakage when the relay is open	I_{LEAK}	---	---	1.0	μA
	Capacity between terminals	C_{OFF}	---	65	---	pF
Capacity between I/O terminals		C_{I-O}	---	0.8	---	pF
Insulation resistance		R_{I-O}	1,000	---	---	$M\Omega$
Turn-ON time	SPST-NO	t_{ON}	---	---	1.0	ms
	SPST-NC	t_{ON}	---	---	1.0	ms
Turn-OFF time	SPST-NO	t_{OFF}	---	---	1.0	ms
	SPST-NC	t_{OFF}	---	---	3.0	ms

Note: 2. Turn-ON and Turn-OFF Times



■ Recommended Operating Conditions




Use the G3VM under the following conditions so that the Relay will operate properly.

Item	Symbol	Minimum	Typical	Maximum	Unit
Load voltage (AC peak/DC)	V_{DD}	---	---	280	V
Operating LED forward current	I_F	5	---	25	mA
Continuous load current (AC peak/DC)	I_O	---	---	120	mA
Operating temperature	T_a	- 20	---	65	°C







■ Engineering Data

G3VM-355CR/FR







Common Characteristics; SPST-NO / SPST-NC



Characteristics; SPST-NO



■ Engineering Data
G3VM-355CR/FR (continued)
Characteristics; SPST-NC



All sales are subject to Omron Electronic Components LLC standard terms and conditions of sale, which can be found at http://www.components.omron.com/components/web/webfiles.nsf/sales_terms.html

ALL DIMENSIONS SHOWN ARE IN MILLIMETERS.

To convert millimeters into inches, multiply by 0.03937. To convert grams into ounces, multiply by 0.03527.

OMRON[®]

**OMRON ELECTRONIC
COMPONENTS LLC**

55 E. Commerce Drive, Suite B
Schaumburg, IL 60173

847-882-2288

OMRON ON-LINE

Global - <http://www.omron.com>

USA - <http://www.components.omron.com>

Cat. No. X302-E-1c

06/13

Specifications subject to change without notice

Printed in USA