# GCM155R71H681KA37#

"#" indicates a package specification code.








< List of part numbers with package codes >

 ${\tt GCM155R71H681KA37D} \ , \ {\tt GCM155R71H681KA37W} \ , \ {\tt GCM155R71H681KA37J}$ 

## Shape



-	Rei	er	er	ices

Packaging	Specifications	Minimum quantity
D	180mm Paper taping	10000
J	330mm Paper taping	50000
W	180mm Paper taping (W8P1*)  * Width: 8mm, Pocket pitch: 1mm	20000

Mass (typ.)			
1 piece	1.6mg		
180mm Reel	118g		

### Specifications

External terminal width e

Size code in inch(mm)

Distance between external terminals g

T size

Capacitance	680pF ± 10%
Rated voltage	50Vdc
Temperature characteristics (complied standard)	X7R(EIA)
Capacitance change rate	± 15.0%
Temperature range of temperature characteristics	-55 to 125
Operating temperature range	-55 to 125

1 of 2

### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it 's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

 $0.5 \pm 0.05$ mm


0.15 to 0.35mm

0.3mm min.


0402 (1005)




Frequency characteristics (ESR, Impedance)




DC bias characteristics




Capacitance - temperature characteristics



S parameter (Smith chart S11)



AC voltage characteristics



2 of 2