


GJM0335C1ER30BB01#

Recommended Reflow OK With RoHS compact HIQ

< List of part numbers with package codes >

GJM0335C1ER30BB01D , GJM0335C1ER30BB01W , GJM0335C1ER30BB01J

Shape





"#" indicates a package specification code.

L size	0.6 ± 0.03mm	
W size	0.3 ± 0.03mm	
T size	0.3 ± 0.03mm	
External terminal width e	0.1 to 0.2mm	
Distance between external terminals g	0.2mm min.	
Size code in mm(inch)	0603 (0201)	
Specifications		
Capacitance	0.30pF ± 0.1pl	
Rated voltage	25Vdc	
Temperature characteristics (complied standard)	COG(EIA)	
Temperature coefficient	0 ± 30ppm/	
Temperature range of temperature characteristics	25 to 125	
	-55 to 125	

Packag	ing Specifications	Minimum quantity
D	180mm Paper taping	15000
J	330mm Paper taping	50000
W	180mm Paper taping (W8P1*) * Width : 8mm, Pocket pitch : 1mm	30000
	Ма	ass (typ.)

180mm Reel

1 piece

1 of 2

🔔 Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it 's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.


Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

0.33mg


118g

Chart of characteristic data (The charts below may show another part number which shares its characteristics.)

Frequency characteristics (ESR, Impedance)




AC voltage characteristics




This PDF data has only typical specifications because there is no space for detailed specifications. Therefore, please reviewour product specifications or consult the approval sheet for product specifications before ordering.

S parameter (Smith chart S11)



Capacitance - temperature characteristics





Last updated: 2013/10/23