

GRM1555C1H160JZ01#

" # " indicates a package specification code.


To be discontinued


Reflow OK

Complies with RoHS

< List of part numbers with package codes >  
GRM1555C1H160JZ01D , GRM1555C1H160JZ01W , GRM1555C1H160JZ01J

Shape





L size

W size

T size

External terminal width e

Distance between external terminals g

Size code in mm(inch)

1.0 ± 0.05mm

0.5 ± 0.05mm

0.5 ± 0.05mm

0.15 to 0.35mm

0.3mm min.

1005 (0402)

Specifications

Capacitance	16pF ± 5%
Rated voltage	50Vdc
Temperature characteristics (complied standard)	COG(EIA)
Temperature coefficient	0 ± 30ppm/
Temperature range of temperature characteristics	25 to 125
Operating temperature range	-55 to 125

Notes

Please use replacements or Recommended.

References


Packaging	Specifications	Minimum quantity
D	180mm Paper taping	10000
J	330mm Paper taping	50000
W	180mm Paper taping (W8P1*) * Width : 8mm, Pocket pitch : 1mm	20000

	Mass (typ.)
1 piece	1.6mg
180mm Reel	118g


 Attention

- 1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it ' s specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2.This datasheet has only typical specifications because there is no space for detailed specifications.
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.


Frequency characteristics (ESR, Impedance)




S parameter (Smith chart S11)



AC voltage characteristics



Capacitance - temperature characteristics



This PDF data has only typical specifications because there is no space for detailed specifications. Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.