


GRM188F51H224ZA01#

Available Flow OK Reflow OK with RoHS

< List of part numbers with package codes > GRM188F51H224ZA01D , GRM188F51H224ZA01J

Shape





10000

6.3mg

144g

"#" indicates a package specification code.

L size			1.6 ±0.1mm	
W size			0.8 ± 0.1mm	
T size			0.8 ± 0.1mm	
External terminal width e			0.2 to 0.5mm	
Distance between external terminals g			0.5mm min.	
Size code in mm(inch)			1608 (0603)	
Specifications	3			
Capacitance			0.22µF +80/-20%	
Rated voltage			50Vdc	
Temperature characteristics (complied standard)			Y5V(EIA)	
Capacitance change rate			+22.0/-82.0%	
Temperature range of temperature characteristics			-30 to 85	
Operating temperature range			-30 to 85	
References				
Packaging		Specifications	Minimum quant	ity
D	180mm Paper taping		4000	
_				

Mass (typ.) 1 piece 180mm Reel

330mm Paper taping

1 of 1

🔔 Attention

J

This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it 's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
This datasheet has only typical specifications because there is no space for detailed specifications.
Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

muRata Murata Manufacturing Co., Ltd.

URL : http://www.murata.co.jp/

Last updated: 2013/10/20