


## GRM2165C1H471JA01#

Available Flow OK Reflow OK with RoHS

< List of part numbers with package codes > GRM2165C1H471JA01D , GRM2165C1H471JA01J

Shape





"#" indicates a package specification code.

L size		2.0 ±0.1mm	
W size		1.25 ±0.1mm	
T size		0.6 ±0.1mm	
External terminal width e		0.2 to 0.7mm	
Distance between external terminals g		0.7mm min.	
Size code in mm(inch)		2012 (0805)	
Specifications			
Capacitance			470pF ±5%
Rated voltage			50Vdc
Temperature characteristics (complied standard)			COG(EIA)
Temperature coefficient			0 ± 30ppm/
Temperature range of temperature characteristics			25 to 125
Operating temperature range			-55 to 125
References			
Packaging	Specifications		Minimum quanti

PackagingSpecificationsMinimum quantityD180mm Paper taping4000J330mm Paper taping10000

1 of 1

## 🔔 Attention

This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it 's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
This datasheet has only typical specifications because there is no space for detailed specifications.
Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

## muRata Murata Manufacturing Co., Ltd.

URL : http://www.murata.co.jp/

Last updated: 2013/10/20