


GRM219R71C224KA01#

Available Flow OK Reflow OK with RoHS

< List of part numbers with package codes > GRM219R71C224KA01D , GRM219R71C224KA01J

Shape





11mg

162g

"#" indicates a package specification code.

Lsize	Э			2.0 ± 0.1mm	
W siz	ze			1.25 ±0.1mm	
T size	e		0.85 ±0.1mm		
Exter	nal terminal width e		0.2 to 0.7mm		
Dista	nce between external	terminals g	0.7mm min.		
Size	code in mm(inch)		2012 (0805)		
Spec	ifications				
Capacitance					0.22µF ±10%
Rated	d voltage			16Vdc	
Temp	perature characteristic	s (complied standard)		X7R(EIA)	
Capacitance change rate					± 15.0%
Temperature range of temperature characteristics					-55 to 125
Operating temperature range					-55 to 125
Refe	rences				
	Packaging		Specifications		Minimum quantity
D		180mm Paper taping		4000	
J		330mm Paper taping		10000)

Mass (typ.) 1 piece 180mm Reel

1 of 1

🔔 Attention

This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it 's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
This datasheet has only typical specifications because there is no space for detailed specifications.
Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

muRata Murata Manufacturing Co., Ltd.

URL : http://www.murata.co.jp/

Last updated: 2013/10/20