GRM32MR72A474KA01#

"#" indicates a package specification code.








< List of part numbers with package codes > GRM32MR72A474KA01L , GRM32MR72A474KA01K

Shape





L size 3.2 ± 0.3 mm 2.5 ± 0.2 mm W size 1.15 ± 0.1 mm T size External terminal width e 0.3mm min. Distance between external terminals g 1.0mm min. Size code in mm(inch) 3225 (1210)

Specifications

Capacitance $0.47 \mu F \pm 10\%$ 100Vdc Rated voltage X7R(EIA) Temperature characteristics (complied standard) Capacitance change rate ± 15.0% Temperature range of temperature characteristics -55 to 125 Operating temperature range -55 to 125

References

Packaging	Specifications			Minimum quantity
L	180mm Embossed taping		3	000
K	330mm Embossed taping		1	0000
		Mass (typ.)		
1 piece			50mg	
180mm Reel			200g	

1 of 1



- 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it 's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



muRata Murata Manufacturing Co., Ltd.

URL: http://www.murata.co.jp/

Last updated: 2013/10/23