



APPLICABLE STANDARD					
RATING	OPERATING TEMPERATURE RANGE	-40 °C TO +105 °C (NOTE1)		STORAGE TEMPERATURE RANGE	-40 °C TO +105 °C
	VOLTAGE	50 V AC		CURRENT	0.5 A
SPECIFICATIONS					
ITEM		TEST METHOD		REQUIREMENTS	QT AT
CONSTRUCTION					
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.		ACCORDING TO DRAWING.	X X
MARKING		CONFIRMED VISUALLY.			X X
ELECTRIC CHARACTERISTICS					
CONTACT RESISTANCE		0.5A DC.		100 mΩ MAX.	X -
CONTACT RESISTANCE MILLIVOLT LEVEL METHOD		20 mV AC MAX, 0.1 mA(DC OR 1000Hz)		100 mΩ MAX.	X -
INSULATION RESISTANCE		250 V DC		500 MΩ MIN.	X -
VOLTAGE PROOF		250 V AC FOR 1 min.		NO FLASHOVER OR BREAKDOWN.	X -
MECHANICAL CHARACTERISTICS					
MECHANICAL OPERATION		30 TIMES INSERTIONS AND EXTRACTIONS.		① CONTACT RESISTANCE: 120 mΩ MAX. ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	X -
VIBRATION		FREQUENCY 20 TO 400 Hz, 43.1 m/s <sup>2</sup> AT 3 h FOR 3 DIRECTIONS.		① NO ELECTRICAL DISCONTINUITY OF 10 μs. ② CONTACT RESISTANCE: 120 mΩ MAX. ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	X -
SHOCK		FREQUENCY 20 TO 50 Hz, 66.6 m/s <sup>2</sup> AT 1 h.		① NO ELECTRICAL DISCONTINUITY OF 10 μs. ② CONTACT RESISTANCE: 120 mΩ MAX. ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	X -
LOCK STRENGTH		APPLYING A PULL FORCE THE MATING AXIALLY AT -N MAX.		① DURING APPLYING, MATING COMPLETELY. ② AFTER APPLYING, NO DEFECT OF MATING PARTS.	- -
ENVIRONMENTAL CHARACTERISTICS					
DAMP HEAT (STEADY STATE)		EXPOSED AT 60 °C, 90 ~ 95 %, 96 h.		① CONTACT RESISTANCE: 120 mΩ MAX. ② INSULATION RESISTANCE: 100 MΩ MIN. ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	X -
RAPID CHANGE OF TEMPERATURE		TEMPERATURE -40→5 TO 35→ 80→5 TO 35°C TIME 30 → 5 → 30 → 5 min UNDER 1000 CYCLES.		① CONTACT RESISTANCE: 120 mΩ MAX. ② INSULATION RESISTANCE: 100 MΩ MIN. ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	X -
DRY HEAT		EXPOSED AT 105°C, 300 h.		① CONTACT RESISTANCE: 120 mΩ MAX. ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	X -
COLD		EXPOSED AT -40°C, 120 h.		① CONTACT RESISTANCE: 120 mΩ MAX. ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	X -
RESISTANCE TO HSO <sup>3</sup> GAS		EXPOSED IN 500 PPM FOR 8h.		① CONTACT RESISTANCE: 120 mΩ MAX. ② NO HEAVY CORROSION.	X -
RESISTANCE TO SOLDERING HEAT		SOLDER TEMPERATURE, 260°C FOR IMMERSION DURATION, 10 s.		NO DEFORMATION OF CASE OF EXCESSIVE LOOSENESS OF THE TERMINALS.	X -
SOLDERABILITY		SOLDERED AT SOLDER TEMPERATURE, 245°C FOR IMMERSION DURATION, 3 s.		A NEW UNIFORM COATING OF SOLDER SHALL COVER A MINIMUM OF 95 % OF THE SURFACE BEING IMMersed.	X -
COUNT	DESCRIPTION OF REVISIONS		DESIGNED	CHECKED	DATE
△0					
REMARK			APPROVED	AR. SHIRAI	10.03.29
(NOTE1) INCLUDE THE TEMPERATURE RISING BY CURRENT.			CHECKED	TY. TAKAHASHI	10.03.29
			DESIGNED	TY. SAKASHITA	10.03.29
			DRAWN	KT. MATSUDA	10.03.26
Note QT:Qualification Test AT:Assurance Test X:Applicable Test			DRAWING NO.		ELC4-167667-00
HRS		SPECIFICATION SHEET		PART NO.	GT23F-50DP-0.8H
		HIROSE ELECTRIC CO., LTD.		CODE NO.	CL773-0008-0-00 △0 1/1

ELV, RoHS COMPLIANT




NOTE 1. CO-PLANARITY SHALL BE 0.1 MAX.  
2. RECOMMENDED SOLDER THICKNESS=0.15



RECOMMENDED TEMPERATURE PROFILE FOR REFLOW

- 1. PEAK : 250°C
- 2. OVER230°C : 60sec MAX
- 3. PREHEAT : 150~200°C, 90~120sec
- 4. NO. OF CYCLES : 2 TIMES MAX

\*This temperature profile is the recommended value. The temperature profile may differ depending on the cream solder, the manufacturer, the PC Board size, and other mounting materials, etc. Please confirm the mounting condition before applying the recommended temperature profile.






Recommended PCB layout




A(4:1)

PACKING STYLE

1. Place connectors into an embossed carrier tape.



2. Put a reel into a cardboard.



W=(405) (mm)  
D=(405) (mm)  
H=(49) (mm)

2	BRASS	Contact:GOLD PLATING. Mounting:TIN PLATING	4	BRASS	TIN PLATING
1	PA	BLACK	3	BRASS	Contact:GOLD PLATING. Mounting:TIN PLATING
NO.	MATERIAL	FINISH , REMARKS	NO.	MATERIAL	FINISH , REMARKS
UNITS mm	SCALE 2 : 1	COUNT 11	DESCRIPTION OF REVISIONS DIS-T-001896	DESIGNED HH. TSUKUMO	CHECKED TY. TAKAHASHI
APPROVED :AR. SHIRAI	10. 03. 29	DRAWING NO.	EDC3-167667-00	DATE	10. 09. 30
CHECKED :TY. TAKAHASHI	10. 03. 29	PART NO.	GT23F-50DP-0. 8H		
DESIGNED :TY. SAKASHITA	10. 03. 29	CODE NO.	CL773-0008-0-00		
DRAWN :KT. MATSUDA	10. 03. 26				