



Part Number

HEN.3M.330.XLNP

Size/Series 3MN / M

[Request a quote](#)

MECHANICAL DETAILS

Shell Style/Model HE*: Fixed receptacle, nut fixing for printed circuit, watertight

Keying

Housing Material Environment friendly aluminium (nickel plated, anthracite color) shell and nut, other pieces bronze/brass

Cable Fixing J : 0 - 0 mm

Variant P : Watertight

	A	C	H	L	N	P	R	S1	S2	e
mm.	23.0	22.8	10.16	20.8	16.8	5.3	13.8	17.5	20.0	M19x1.00
in.	0.91	0.90	0.40	0.82	0.66	0.21	0.54	0.69	0.79	

PERFORMANCE DETAILS

Specifications

Contact Type: Print (straight)

Max. Matings: 5000

Contact Dia.: 0.7 mm (0.028in)

R (max): 6.1 mOhm

OTHER CHARACTERISTICS

Humidity (max): <=95% [at 60 deg C /140 F]

Vibration: 15 g [10 Hz - 2000 Hz]

Shock Resistance: 100 g [6 ms]

Operating temperature: -55°C/ +200°C

Climatical Category: 15/200/21 (Al. shell)

Lighting strike EIA 364-75 10K amps - 6 times

EMI Shielding EIA 364-66A - 1Ghz-80 dB,3GHz-70 dB,6GHz- 58dB

R leak (He) (max): 0.000001 mbar*l/s (if vacuum-tested)

IP Rating 68

Catalog

