

Part Search



Part Number . . .

HGP.00.250.CTLP



Size/Series 00 / 00

[Demande d'offres](#)

MECHANICAL DETAILS

Shell Style/Model HGP*: Fixed receptacle, nut fixing, watertight
Keying Circular (can rotate)
Housing Material Brass (chrome plated) shell and collet nut, nickel plated brass latch sleeve and mid pieces
Cable Fixing J : 0 - 0 mm
Variant P : Watertight

	A	B	L	S3	Weight	e
mm.	11	10.2	17	9	4.2	M7x0.5
in.	0.43	0.40	0.67	0.35	0.17	



[Copyright](#) [Privacy policy](#) [Product safety](#)

MECHANICAL DETAILS

Insert Configuration 0.25 : 1 Coax (50 Ohm)
Insulator T: PTFE
Specifications
Contact Type: Coaxial 50 Ohm (Solder)
Max. Matings: 5000
Contact Dia.: 0.7 mm (0.028in)
Bucket Dia.: 0.6 mm (0.024in)
R (max): 6.1 mOhm
Vtest: 2100 V (AC), 3000 V (DC)
Rated Current: 4 A (AC/DC)
Impedance: 50 Ohm
VSWR: 1.09 + 0.11 * f/GHz

MECHANICAL DETAILS

Endurance (Shell) 3839 mating cycles
F ret (min): 100 N
R leak (He) (max): 0.000001 mbar*l/s (if vacuum-tested)
Pressure 60 bars
IP Rating 68
Catalog



[Download 3D draw](#)

