





- NOTE.
- 1 Mounting side is mated with the receptacle:IT3M-300S-BGA(**) and fixed with the latch.
 - 2 Lot No. shall be marked on the indicated position.
 - 3 The indicated mother board and daughter card shall be fastened to the additional reinforcements to prevent the stress on IT3*-300S-BGA(**) solder joints.
 4. More information of this product is available in HIROSE document :ETAD-F0347 "IT3 design guideline".
 5. This product consists of 300 signal lines and 270 ground lines.
 6. 30pcs of this products are packed in a soft tray.
 7. Standard package of 60pcs are packaged in a carton box.

3	LCP	BLACK	UL94V-0						
2	LCP	GRAY	UL94V-0	5	Copper Alloy	CONTACT AREA:NICKEL(1.5μm)+GOLD (0.75μm)			
1	PBT	BLACK	UL94V-0	4	Copper Alloy	CONTACT AREA:NICKEL(1.5μm)+GOLD (0.75μm)			
NO.	MATERIAL	FINISH:	REMARKS	NO.	MATERIAL	FINISH:	REMARKS		
UNITS mm		SCALE 2 : 1		COUNT	DESCRIPTION OF REVISIONS		DESIGNED	CHECKED	DATE
 HIROSE ELECTRIC CO., LTD.		APPROVED : TM. MATSUO		09. 07. 29	DRAWING NO.		EDC3-325919-01		
		CHECKED : MK. EZAKI		09. 07. 29	PART NO.		IT3-300P-22H(03)		
		DESIGNED : TS. SAITO		09. 07. 29	CODE NO.		CL636-0210-2-03		
		DRAWN : TS. SAITO		09. 07. 29			 1/1		