

Customer Information Sheet

DRAWING No.: M80-667XXXX

SHEET 2 OF 2





IF IN DOUBT - ASK

(C)

NOT TO SCALE

THIRD ANGLE PROJECTION

ALL DIMENSIONS IN mm



ORDER CODE:

M80-667XXXX

No. OF CONTACTS

04, 06, 08, 10, 12, 14,
16, 18, 20, 26, 34, 44

FINISH

22 - GOLD, 90/10 TIN/LEAD
42 - GOLD, 100% TIN
45 - ALL OVER GOLD

SPECIFICATIONS:

MATERIAL:

MOULDING = GLASS-FILLED POLYAMIDE 46, UL94V-0, BLACK

CONTACT = BRASS

LATCH = BERYLLIUM COPPER

FINISH:

CONTACT:

22 = 0.75μ GOLD ON CONTACT AREA,

0.3μ 90/10 TIN/LEAD ON TAILS

42 = 0.75μ GOLD ON CONTACT AREA,

0.3μ 100% TIN ON TAILS

45 = 0.75μ GOLD OVER NICKEL

LATCH = 1.25μ NICKEL

ELECTRICAL:

CURRENT RATING AT 25°C = 3.0A MAX

CURRENT RATING AT 85°C = 2.2A MAX

WORKING VOLTAGE = 800V AC/DC

VOLTAGE PROOF = 1200V AC/DC

CONTACT RESISTANCE = $25 \text{ m}\Omega$ MAX

INSULATION RESISTANCE = $100 \text{ M}\Omega$ MIN

MECHANICAL:


DURABILITY = 500 OPERATIONS

ENVIRONMENTAL:

TEMPERATURE RANGE = -55°C TO $+125^\circ\text{C}$

PACKING:

TUBE, 2-OFF STRAIN RELIEF STRAPS PER CONNECTOR IN BAG
FOR COMPLETE SPECIFICATION, SEE COMPONENT
SPECIFICATION C005XX (LATEST ISSUE)



RECOMMENDED
PCB LAYOUT

SB	4	12.03.12	11682
NAME	ISS.	DATE	C/NOTE
APPROVED:		S.BENNETT	
CHECKED:		M.G.PLESTED	
DRAWN:		B. M. KENT	
CUSTOMER REF.:			
ASSEMBLY DRG:			

HARWIN

www.harwin.com
technical@harwin.com

THIS DRAWING AND ANY
INFORMATION OR DESCRIPTIVE
MATTER SET OUT HEREON ARE
CONFIDENTIAL AND COPYRIGHT
PROPERTY OF THE HARWIN
GROUP AND MUST NOT BE
DISCLOSED, LOANED, COPIED
OR USED FOR MANUFACTURING,
TENDERING OR FOR ANY
OTHER PURPOSE WITHOUT
THEIR WRITTEN PERMISSION.

TOLERANCES

X. = $\pm 1\text{mm}$

X.X = $\pm 0.25\text{mm}$

X.XX = $\pm 0.10\text{mm}$

X.XXX = $\pm 0.01\text{mm}$

ANGLES = $\pm 5^\circ$

UNLESS STATED

MATERIAL:

SEE ABOVE

FINISH:

SEE ABOVE

S/AREA:

mm²

TITLE:

STANDARD DATAMATE
DIL HORIZONTAL SMT MALE
ASSEMBLY (FRICTION LATCH)

DRAWING NUMBER:

M80-667XXXX

SHT
2 OF 2