


Metal Core Wire-wound Chip Power Inductors (MCOIL(TM) MA series)

MAMK2520TR47M



■ Features

- Item Summary
0.47 μ H($\pm 20\%$), 4200mA, 3400mA
- Lifecycle Stage
Mass Production
- Standard packaging quantity (minimum)
Taping 3000pcs

■ Products characteristics table


CaseSize (EIA/JIS)	~/2520
Inductance	0.47 μ H($\pm 20\%$)
Inductance Measuring Frequency	2MHz
Rated Current -Saturation Current	4200mA
Rated Current -Temperature Rise Current	3400mA
DC Resistance (max)	0.039 Ω
Temperature Range	-40°C to 105°C
RoHS Compliance	Yes
Halogen Free	Yes
Soldering Method	Reflow

■ External Dimensions

L	2.5mm ± 0.2
W	2mm ± 0.2
H	1.2mm max

■ Recommended Land Patterns

【推奨ランドパターン】 実装上の注意 ・実装状態を確認の上で使用するようお願いします。 ・本製品のはんだ付けはリフローはんだ工法に限ります。
【Recommended Land Patterns】 Surface Mounting ・Mounting and soldering conditions should be checked beforehand. ・Applicable soldering process to these products is reflow soldering only.

Metal Core Wire-wound Chip Power Inductors (MCOIL_{TM} MA series)

Type	A	B	C
2016	0.7	0.8	1.8
2520	0.8	1.2	2.0

unit:mm