



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: N032-001

Cat5e Straight Through Modular In-line Coupler (RJ45 F/F)

Highlights

- Premium cabling for Category 5 and 5e applications — rated for 350 MHz/1Gbps communications



Description

Tripp Lite's category 5e stand alone RJ45 straight inline coupler provides a female-to-female feed-through connection. It allows you to extend the length of a category 5e patch cable by adding another category 5e patch cable.

Package Includes



- Cat5e Straight Thru Modular Coupler RJ45F to RJ45F

Features

- For category 5 and 5e applications
- Use to connect two patch cables for a longer cable length
- Straight through design

Specifications

OVERVIEW	
Intended Application	Computer Networking
Cable Type	CAT5 / CAT5E
Model Type	In-Line Couplers
UPC ASSIGNMENT	
Unit Carton UPC#	037332013149
PHYSICAL	
Style	Cat5/5e
CONNECTIONS	

Connector A	 RJ45 (FEMALE)
Connector B	 RJ45 (FEMALE)
WARRANTY	
Product Warranty Period (Worldwide)	Lifetime limited warranty

Related Items

Optional Products

Related Model	Description	Qty.
N002-003-GY	3-ft. Cat5e 350MHz Molded Cable (RJ45 M/M) - Gray	1
N002-005-GY	5-ft. Cat5e 350MHz Molded Cable (RJ45 M/M) - Gray	1
N002-007-GY	7-ft. Cat5e 350MHz Molded Cable (RJ45 M/M) - Gray	1
N002-010-GY	10-ft. Cat5e 350MHz Molded Cable (RJ45 M/M) - Gray	1
N002-014-GY	14-ft. Cat5e 350MHz Molded Cable (RJ45 M/M) - Gray	1
N002-025-GY	25-ft. Cat5e 350MHz Molded Cable (RJ45 M/M) - Gray	1
N002-050-GY	50-ft. Cat5e 350MHz Molded Cable (RJ45 M/M) - Gray	1

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=2145.

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.