

SMD Power Inductors (NR series)

NR5040T2R2N



■ Features

- Item Summary
2.2 μ H($\pm 30\%$), 4600mA, 3500mA
- Lifecycle Stage
Mass Production
- Standard packaging quantity (minimum)
Taping 1500pcs

■ Products characteristics table


CaseSize (EIA/JIS)	~/5040
Inductance	2.2 μ H($\pm 30\%$)
Inductance Measuring Frequency	100kHz
Rated Current -Saturation Current	4600mA
Rated Current -Temperature Rise Current	3500mA
DC Resistance (max)	0.0286 Ω
Avg. of DC.Resistance	0.022 Ω
Temperature Range	-25°C to 120°C
Self-resonant Frequency (min)	42MHz
RoHS Compliance	Yes
Halogen Free	Yes
Soldering Method	Reflow

■ External Dimensions

L	4.9mm ± 0.2
W	4.9mm ± 0.2
H	4.1mm max

■ Recommended Land Patterns

【推奨ランドパターン】 実装上の注意 ・実装状態を確認の上ご使用ください。また、ご購入の際は、 本製品のほんたひは、リフローはんだ工法に準じます。	
【Recommended Land Patterns】 Surface Mounting ・Mounting and soldering conditions should be checked beforehand. ・Applicable soldering process to these products is reflow soldering only.	



SMD Power Inductors (NR series/NR series H type/S type /V type)			
Type	A	B	C
NR50010			
NR50012			
NR50014			
NR50020	1.5	3.6	4
NR50024			
NR50030			
NR 5040, NR5040			

unit:mm