




Non EMC DIN-Based VectorPak™ Subracks



P/N CG1-160 and CG1-220 card guides are injection molded




Black/Noryl with anodized aluminum
Aluminum - "U" type


Card Guides

Specially designed card guides provide easy installation and repositioning, without special tools. Material is 5% glass-filled polycarbonate. Package contains 12 guides. Secure installation by spring loaded retainer ledge on front rail extrusion and vertical insertion into rear extrusion holes.

Part No.	Description	Card Thick	Description
CG1-160/12	160mm	.062"	Glass filled Noryl injection molded
CG1-220/12	220mm	.062"	Glass filled Noryl injection molded
CG1-280U/12	280mm	.062"	Noryl/Black anodized aluminum
CG1-340U/12	340mm	.062"	Noryl/Black anodized aluminum
CG1-400U/12	400mm	.062"	Noryl/Black anodized aluminum



Installation/removal of guides from front strut



Handles

Black Anodized Aluminum handles for 3 and 6 subracks. (Mounting hardware included).

Part No.	Pkg. Qty	Description
HA19-3U	2	Handle for 3U subrack, 8-32 tapped holes
HA19-6U	2	Handle for 6U subrack, 8-32 tapped holes

Dress Panels

Dress panels provide an attractive, finished look for Vector Card Cages and are required when adding handles. Mounting hardware included. Brushed Aluminum with clear irridite finish.

Part No.	Pkg. Qty	Description
DP-3U	2	For 3U Subrack, 5.25" high X 1.10" wide
DP-6U	2	For 6U Subrack, 10.50" high X 1.10" wide
DP-9U	2	For 9U Subrack, 15.75" high X 1.10" wide

Top/Bottom Covers

These aluminum panels provide maximum protection for cards and are available in perforated (AC160-84-1) or solid (AC160-84-2). Covers slide easily into DIN extrusion grooves and can be added or removed at any time, no hardware needed. Made of brushed aluminum with clear irridite finish.

Part No.	Pkg Qty	Width	Depth	For Card Size
*				
AC160-84-1, 2	2	16.98"	4.93"	160mm
AC220-84-1, 2	2	16.98"	7.29"	220mm
AC280-84-1, 2	2	16.98"	9.65"	280mm
AC340-84-1, 2	2	16.98"	12.01"	340mm
AC400-84-1, 2	2	16.98"	14.37"	400mm

*substitute -1 with
-2 for solid covers



VectorPak™ powered subrack
with VME J1/J2 backplane and integrated fans



Specification subject to change without notice

www.vectorelect.com

Note: 1" = 25.4mm, 1U = 1.75"

Specification subject to change without notice

800-423-5659