



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: OMNISMART700HG

Omni Smart UPS System - Line-interactive, tower battery backup with hospital grade plug and receptacles

Highlights

- 700VA line interactive tower UPS system
- Hospital grade plug and 4 NEMA5-15R hospital grade output receptacles
- Corrects brownouts and overvoltages from 75 to 147V without using battery power
- Enhanced DB9 communications port

Description

Tripp Lite's OMNI SMART 700HG offers UPS protection, built-in line interactive voltage regulation, intelligent monitoring and unattended shutdown capability. 700VA power handling capacity supports computers, internetworking equipment and other critical loads during commercial power failures. Line interactive voltage regulation corrects brownouts as low as 75V and overvoltages as high as 147V back to normal 120V levels, saving battery reserves for use only during complete power failures. Includes 4 hospital grade outlets, diagnostic LEDs and built-in DB9 communications port that works with web downloadable PowerAlert Software and cabling to provide automatic unattended shutdown of connected network and PC applications.

Applications

- Ideal UPS protection for network workstations, small office file servers and PC systems

Package Includes

- OMNI SMART 700HG UPS System
- RS-232 monitoring cable
- Warranty information
- Instruction manual

Features

- Ideal UPS protection for mission critical equipment and computers where hospital-grade input/output connections are required
- Provides connected equipment with continuous power during short and long duration loss of commercial power
- Line-interactive voltage regulation corrects brownouts and overvoltages from 75 to 147 volts back to usable 120v output levels, without using battery power
- Hospital-grade plug and outlets offer added degree of safety to input/output connections
- Supports loads up to 700VA/425 watts
- 22 minutes half load runtime (with 350VA load), 9 minutes full load runtime (with 700VA load)
- Hospital grade input plug and 4 NEMA5-15R hospital grade output receptacles
- 1-DB9 serial port for network interface; SNMP compatible
- Surge protection and EMI/RFI noise filtering
- PowerAlert UPS monitoring and auto-shutdown software available for free download from www.tripplite.com
- Includes complete cabling for remote monitoring via PowerAlert software
- 4 diagnostic LEDs indicate AC present, on battery, voltage correction & battery low/replace
- Battery replacement door
- 2 year product warranty

Specifications

OUTPUT

Frequency compatibility	60 Hz
Output VA	700
Output watts	425
Output nominal voltage	120V nominal
Output voltage regulation	LINE MODE: Sine wave line voltage 120V (-18% / +8%) BATTERY MODE: PWM sine wave output 120V +/-5%
Output frequency regulation	LINE MODE: Passes line frequency of 60Hz +/-10% BATTERY MODE: Inverter output regulated to 60Hz +/-0.5Hz
Outlet quantity / type	4 NEMA5-15R HG
INPUT	
UPS Input cord length (ft.)	6 ft, 14 gauge
Recommended Electrical Service	15A 120V
Maximum Input Amps (A)	3.8
Maximum Input Watts	460
Input connection type	NEMA 5-15P Hospital-Grade
Voltage compatibility (VAC)	120
BATTERY	
DC system voltage (VDC)	12
Battery Access	Battery access door allows hot swap battery replacement without powering connected equipment off
Full load runtime	9 minutes (700VA)
Half load runtime	22 minutes (350VA)
Replacement Battery Cartridge	RBC52 (quantity 2)
Typical battery lifespan	3-6 years, depending on usage
Battery charge	2-4 hours to 90%
VOLTAGE REGULATION	
Voltage regulation description	Automatic Voltage Regulation (AVR) circuits maintain clean, regulated computer-grade 120V nominal output, without using battery power, during brownouts to 75V and overvoltages to 147V
Overvoltage correction	Input voltages between 128 and 147V AC are reduced by 12%
Brownout correction	Input voltages between 93 and 107V AC are boosted by 14%
Severe brownout correction	Input voltages between 75 and 92V AC are boosted by 30%
Direct pass through	Input voltages between 108 and 127V AC are passed on to connected equipment unchanged
LEDS ALARMS & SWITCHES	
Alarms	Audible alarm indicates power failure conditions, silenceable via alarm cancel switch. Once cancelled, alarm will resume when approximately 2 minutes of battery operation remain (assuming full load).

Switches	Yes, includes 2 front panel mounted push-button switches for system enable, self-test and alarm cancel functions
Front panel LEDs	4 front-panel indicator LEDs to display line power status, battery power status, battery low/replace status and voltage regulation operation
SURGE / NOISE SUPPRESSION	
EMI / RFI AC noise suppression	Yes
AC suppression response time	Instantaneous
Dataline suppression	-
PHYSICAL	
Shipping weight (lbs)	22
Shipping weight (kg)	10.0
Unit Dimensions (HWD/in)	10.75 x 5.25 x 7.25
Unit Dimensions (HWD/cm)	27.3 x 13.3 x 18.4
Unit weight (lbs)	20
Unit weight (kg)	9.1
Cooling method	Convection
Material of construction	PVC
Form factors supported	Tower
ENVIRONMENTAL	
Relative Humidity	0 to 95%, non-condensing
COMMUNICATIONS	
Network monitoring port	DB9
Software and cabling included	PowerAlert UPS monitoring software available for free download from www.tripplite.com , includes complete RS-232 cabling
LINE / BATTERY TRANSFER	
Transfer time from line power to battery mode	2-4 milliseconds
Low voltage transfer to battery power	75V (resets to line power as voltage increases to 79V)
High voltage transfer to battery power	147V (resets to line power as voltage decreases to 143V)
SPECIAL FEATURES	
Appearance	Attractive gray tower UPS
Cold Start	Yes, inverter can be "cold started" to enable temporary AC output during a power failure
CERTIFICATIONS	
Certifications	Tested to UL1778 (USA, Series AGOM700KSR61), cUL (Canada), FCC Class A (emissions)
WARRANTY	

Product Warranty Period (Worldwide)	2-year limited warranty
Optional Coverage	3 year, 5 year, next day and on-site warranty coverage available

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=22.

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.