



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: P942-19I

19-inch Serial ATA Right Angle (SATA) Signal Cable (7Pin/7Pin-Down)



Highlights

- Connect your high-speed Serial ATA device to a Serial ATA controller
- Support data transfer rates of up to 6.0 Gbps
- Cable is shielded to protect against EMI/RFI

Description

Tripp Lite expands its line of hard drive cables with the introduction of our new line of serial ATA cables. The signal cables connect any high speed Serial ATA device to a Serial ATA controller. Serial ATA delivers two significant benefits: it support much higher data transfer rates (up to 6.0 Gbps...backward compatible to 1.5Gbps) and the narrow cable design helps improve internal air flow. Perfect for the desktop or server that has multiple drives. These cables feature 7-pin straight/7-pin right-angle key down female connectors and offer easy installation.

System Requirements

- Serial ATA device
- Serial ATA controller

Package Includes

- 19-in. Serial ATA Right Angle (SATA) Signal Cable 7Pin/7Pin, Straight/Down

Features

- Connect your high-speed Serial ATA device to a Serial ATA controller
- Support data transfer rates of up to 6.0 Gbps
- Narrow cables design: 1) simplifies cable routing and installation 2) improves air flow within CPU (no more big ribbons blocking air movement)
- Meets Serial ATA 1.0 standards, including Errata 029
- Cable is shielded to protect against EMI/RFI

Specifications

OVERVIEW	
Intended Application	Connecting Peripherals
Cable Type	SATA
INPUT	
Cable Length (in.)	19

UPC ASSIGNMENT	
Unit Carton UPC#	037332120076
PHYSICAL	
Color	Red
Style	SATA
CONNECTIONS	
Connector A	 7 PIN SATA STRAIGHT (MALE)
Connector B	 7 PIN SATA RT. ANGLE DOWN (MALE)
Number of Connectors	2
CERTIFICATIONS	
Certifications	RoHS-Compliant
WARRANTY	
Product Warranty Period (Worldwide)	Lifetime limited warranty

Related Items

Optional Products

Related Model	Description	Qty.
P940-19I	19-inch Serial ATA (SATA) Signal Cable (7Pin/7Pin)	1
P940-39I	39-inch Serial ATA (SATA) Signal Cable (7Pin/7Pin)	1
P943-19I	19-inch Serial ATA (SATA) Signal Cable (7Pin-Up/7Pin-Down)	1
P944-06I	6-inch Serial ATA (SATA) Power Cable (4Pin to 15pin)	1
P946-12I	12-inch Serial ATA (SATA) Dual Power Adapter Cable (4pin/2x15pin SATA)	1

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=2709.

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.