

# Part Search



Part Number  .  .  .

PCA.00.250.CTLC29


Size/Series 00 / 00

Demande d'offres

## MECHANICAL DETAILS

**Shell Style/Model** PCA\*: Free receptacle with cable collet  
**Keying** Circular (can rotate)  
**Housing Material** Brass (chrome plated) shell and collet nut, nickel plated brass latch sleeve and mid pieces  
**Cable Fixing** C29: 2.8 - 3.1 mm **NEW COLLET**  
**Variant** :

|     | A    | L    |
|-----|------|------|
| mm. | 6.5  | 25   |
| in. | 0.26 | 0.98 |



## MECHANICAL DETAILS

**Insert Configuration** 0.25 : 1 Coax (50 Ohm)  
**Insulator** T: PTFE  
**Specifications**  
**Contact Type:** Coaxial 50 Ohm (Solder)  
**Max. Matings:** 5000  
**Contact Dia.:** 0.7 mm (0.028in)  
**Bucket Dia.:** 0.6 mm (0.024in)  
**R (max):** 6.1 mOhm  
**Vtest:** 2100 V (AC), 3000 V (DC)  
**Rated Current:** 4 A (AC/DC)  
**Impedance:** 50 Ohm  
**VSWR:** 1.09 + 0.11 \* f/GHz  
**Cable type:** RG 316 /U

## MECHANICAL DETAILS

**Endurance (Shell)** 3839 mating cycles  
**F ret (min):** 100 N  
**IP Rating** 50  
**Catalog**



[Download 3D draw](#)



[Copyright](#) [Privacy policy](#) [Product safety](#)