



RECOMMENDED P.C.B. LAYOUT
(COMPONENT SIDE OF BOARD)

LOCATE HOLES
⌀ .005 [0.13]
HOLE POSITIONS
ARE BASIC

MATERIALS:

- HOUSING: ENGINEERING THERMOPLASTIC
FLAMMABILITY RATING UL94V-0
COLOR: BLACK
- CONTACTS: PHOSPHOR BRONZE
- PLATING: REFER TO PART NUMBER FOR GOLD THICKNESS
ON MATING SURFACE
50 MICROINCH [1.27 MICRONS] MIN. NICKEL OVERALL
100 MICROINCH [2.54 MICRONS] MIN. MATTE-TIN
OR GOLD FLASH OVER TAIL
- SHIELD: COPPER ALLOY WITH NICKEL PLATED

PART NUMBER: R J E 0 6 - 1 8 8 - 1 X 2 0

SERIES: R J E 0 6
1 PORT: 1
NO. OF POSITIONS: 8
NO. OF CONTACTS: 8

STANDARD
WITH FLANGE
GOLD PLATING
1 = 6 MICROINCH
2 = 15 MICROINCH
3 = 30 MICROINCH
4 = 50 MICROINCH
FULL SHIELD

DRAWN PAULW	DATE MAY15/06
DESIGNED	
CHECKED CHIGOW	MAY15/06
I. E. APPRD.	
Q. A. APPRD.	
DWG. APPRD.	
ENG. REL. NO.	
REF. EAR # A060504	
DIMENSIONS ARE IN INCHES [mm]	03554

Amphenol Canada Corp.			
TITLE RJE06 SERIES, 8 POSITION 8 CONTACT, VERTICAL MOUNT, WITH SHIELD, AND FLANGE - RoHS COMPLIANT			
DWG	DRAWING NO.	REV.	
	P-RJE06-188-1X20	C	
SCALE	WT.	SURF.	SHEET 1 OF 1

THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION AND SUCH INFORMATION
MAY NOT BE DISCLOSED TO OTHERS FOR ANY PURPOSE OR USED FOR MANUFACTURING
PURPOSES WITHOUT WRITTEN PERMISSION FROM AMPHENOL CANADA CORP.