






Customer Information Sheet


DRAWING No.: S1721-XX SHEET 2 OF 2 IF IN DOUBT - ASK (C) NOT TO SCALE THIRD ANGLE PROJECTION ALL DIMENSIONS IN mm



COMPONENT SPECIFICATION:
MATERIAL = BERYLLIUM COPPER
FINISH = '06' = 3μ 90/10 TIN/LEAD
'46' = 3μ 100% TIN,
OVER 2.0μ NICKEL
SHIELD THICKNESS = 0.13-0.23mm

PERFORMANCE SPECIFICATION:
ENGAGEMENT FORCE = 5N MAX.
DISENGAGEMENT FORCE = 0.35N MIN.
DURABILITY = 15 ACTUATIONS MIN.
CONTACT RESISTANCE = 40mΩ MAX.

NOTES:
1. FOR TAPE AND REELED VERSION, SEE DRAWING S1721-06R.
2. PACKING:- 100 COMPONENTS PER BAG
NB: COMPONENTS SUPPLIED IN TAPE POCKETS TO
AVOID DAMAGE DURING STORAGE AND TRANSIT.



PART No.	FINISH:
S1721-06	90/10 TIN/LEAD
S1721-46	100% TIN

SF	5	27.06.13	12129
NAME	ISS.	DATE	C/NOTE
APPROVED:	S.FLOWER		
CHECKED:	M.PLESTED		
DRAWN:	J. ENRIGHT		
CUSTOMER REF.:			
ASSEMBLY DRG:			



THIS DRAWING AND ANY
INFORMATION OR DESCRIPTIVE
MATTER SET OUT HEREON ARE
CONFIDENTIAL AND COPYRIGHT
PROPERTY OF THE HARWIN
GROUP AND MUST NOT BE
DISCLOSED, LOANED, COPIED
OR USED FOR MANUFACTURING,
TENDERING OR FOR ANY
OTHER PURPOSE WITHOUT
THEIR WRITTEN PERMISSION.

TOLERANCES
X. = ±1mm
X.X = ±0.25mm
X.XX = ±0.10mm
X.XXX = ±0.01mm
ANGLES = ±5°
UNLESS STATED

MATERIAL:
SEE ABOVE
FINISH: SEE ABOVE
S/AREA: mm²

TITLE:
MINI SMT RFI SHIELD CLIP
(LOOSE)
DRAWING NUMBER:
S1721-XX
SHT
2 OF
2