

NEW!

PTH

Pneumatic Cable Tie Installation Tools — PTS, PTH Ergonomic Tools

The pneumatic operation and ergonomic design of the PTS and the PTH cable tie installation tools improve productivity by reducing operator fatigue and repetitive motion injuries. These tools provide fast, consistent installation of subminiature through heavy cross section cable ties. They also provide a flush cable tie cut-off that prevents damage to adjacent wire bundles and protects workers' hands and arms for a safe and reliable installation. These innovative pneumatic tools are part of the complete line of *PANDUIT* cable ties and installation tooling that offer customers the preferred bundling solution.



PTS

*PTS tool installs Subminiature (8 Lbs.) through Standard (50 Lbs.) cross section cable ties
PTH tool installs Standard (50 Lbs.) through Heavy (175 Lbs.) cross section cable ties*

Key Features

Benefits

<i>Pneumatic operation and ergonomic design</i>	Tools are comfortable and easy to use; reducing operator fatigue and repetitive motion injuries; improve productivity by minimizing downtime and providing lowest installed cost
<i>Tension and cut-off mechanism</i>	Maintains desired tension for reliable installation; consistently provides flush cable tie cut-off in less than one second, preventing damage to adjacent wire bundles and protecting workers' hands and arms
<i>Controlled tip ejection</i>	Allows operator to quickly and safely remove excess cut-off material; increases productivity by eliminating need to clean-up work area after completion of installation
<i>Beveled tie entry and narrow nose</i>	Quick side entry of tie into tool speeds installation and narrow nose permits easy access to confined areas; maximize application flexibility and increase productivity
<i>Coarse and fine tension adjustment knobs</i>	Allow operator to quickly adjust applied tension to match cable tie cross section being installed; increase productivity when applying multiple cross sections
<i>Two retractable hangers</i>	Allow for hanging the tool in the work area for improved productivity and safe storage of tool when not in use
<i>Quick disconnect fitting</i>	Allows operator to easily connect tool to any air supply source within facility; improves portability and increases productivity

Pneumatic Cable Tie Installation Tools – PTS and PTH Ergonomic Tools



Easy Adjustment

Tension Adjustment

- Quickly change setting to install appropriate cross section cable ties
- Conveniently located at rear of tool for easy access

Step 1: Use the coarse adjustment knob to select the appropriate cable tie cross section.

Step 2: Use the fine adjustment knob, located in front of coarse adjustment knob, to set and maintain desired tension.

Ordering Information

Part Number	Part Description	Packaging	
		Std. Pkg. Qty.	Std. Ctn. Qty.
Pneumatic Ergonomic Tools			
PTS	Pneumatic hand tool. Operates on 70-90 psig, non-lubricated air without special maintenance. Installs the following cable tie cross sections: Subminiature (8 Lbs.); Miniature (18 Lbs.); Intermediate (40 Lbs.); Standard (50 Lbs.). Weight: 17.3 oz. (490g); Gray plastic molded housing; black trigger button; black selector knob.	1	—
NEW! PTH	Pneumatic hand tool. Operates on 70-100 psig, non-lubricated air without special maintenance. Installs the following cable tie cross sections: Standard (50 Lbs.); Heavy-Standard (85 Lbs.); Light-Heavy (120 Lbs.); Heavy (175 Lbs.) Weight: 32.0 oz. (907g); Gray plastic molded housing; red trigger button; red selector knob.	1	—



PTS

Tool Accessories

PL289N1	Filter / Regulator 0.5 micron element, regulated range 3-100 psig, features 1/8" NPT female output port (to Hose, PPH10) and 1/4" male quick disconnect to source air line. Use with PTS and PTH.	1	—
PPH10	Hose Assembly 10 ft. (3M) – Regulator to tool. Includes a 1/8" NPT male connector (to regulator) and 1/8" female quick disconnect (to tool). Use with PTS and PTH.	1	—
PHCAQ	Adapter Fitting for 10 ft. (3M) Hose (PPH10) to regulator with 1/4" female quick disconnect output, features 1/8" NPT female connection (to hose) and 1/4" male quick disconnect (to regulator). Use with PTS and PTH.	1	—
PHCAT	Adapter Fitting for 10 ft. (3M) Hose (PPH10) to regulator with 1/4" NPT female output port, features 1/8" NPT female connection (to hose) and 1/4" NPT male connection (to regulator). Use with PTS and PTH.	1	—
KPTSTL	Tension Locking Kit. Cover to prevent changing tension settings. Consists of lockout cap and screw. Use with PTS and PTH.	1	10
KGTSBLD	Blade Replacement Kit. Can be part of scheduled maintenance plan or when cable tie cut-offs are not clean and crisp. Consists of threadlocker, screw and replacement blade. Use with PTS.	1	10
KPTHBLD	Blade Replacement Kit. Can be part of scheduled maintenance plan or when cable tie cut-offs are not clean and crisp. Consists of threadlocker, screw and replacement blade. Use with PTH.	1	10
GHH	Hand Tool Holster. Durable leather construction with rivets and extra tie-down strap to hold tool in place. Easily fits on belt. Use with PTS.	1	—



PTH



PL289N1, PPH10



KPTSTL



KPTHBLD



GHH

WORLDWIDE SUBSIDIARIES AND SALES OFFICES

PANDUIT CANADA
Markham, Ontario
cs-cdn@panduit.com
Phone: 800.777.3300

PANDUIT EUROPE LTD.
London, UK
cs-emea@panduit.com
Phone: 44.20.8601.7200

PANDUIT SINGAPORE PTE. LTD.
Republic of Singapore
cs-ap@panduit.com
Phone: 65.6379.6700

PANDUIT JAPAN
Tokyo, Japan
cs-japan@panduit.com
Phone: 81.3.3767.7011

PANDUIT LATIN AMERICA
Jalisco, Mexico
cs-la@panduit.com
Phone: 52.333.666.2501

PANDUIT AUSTRALIA PTY. LTD.
Victoria, Australia
cs-aus@panduit.com
Phone: 61.3.9794.9020

For a copy of PANDUIT product warranties, log on to www.panduit.com/warranty



For more information
Visit us at www.panduit.com/ctcb13
Contact Customer Service by email: cs@panduit.com
or by phone: 800-777-3300 and reference CTCB13

©2006 PANDUIT Corp.
ALL RIGHTS RESERVED.
Printed in the U.S.A.
Product Bulletin Number SA-CTCB13
1/2006