

SEE TABLE FOR RECOMMENDED STUD SIZE

E

B $\pm .01$ (.25)

F REF.

C REF.

D

A $\pm .01$ (.25)

PANDUIT PART NO. *	BUNDLE DIA.		A In (mm)	B In (mm)	C In (mm)	D In (mm)	E In (mm)	F In (mm)	MIN. LOOP TENSILE lbs (N)	CROSS- SECTION	RECM. STUD SIZE		WEIGHT lbs/100pcs (g)
	MIN. IN (mm)	MAX. IN (mm)									STUD	LENGTH (min.)	
PLST4H-S25	.18 (4.8)	4.00 (102.)	.075 (1.9)	.300 (7.6)	.94 (23.9)	.265 (6.7)	.515 (13.1)	15.3 (389)	120 (534)	HEAVY	1/4-20	.25	1.44 (654)

*1) SEE CURRENT PRICE SHEET FOR PART NUMBER SUFFIX DESIGNATION FOR PACKAGE SIZE AND PART COLOR.

DIMENSIONS IN PARENTHESES ARE IN METRIC UNITS.

PANDUIT CORP. TINLEY PARK, ILLINOIS

STUD MOUNT CABLE TIE
PLST4H SERIES

UNLESS OTHERWISE SPECIFIED,
DIMENSIONAL TOLERANCES ARE:
(.X) ± .005 (XXX) ± .020 (.5)
(.XX) ± .02 (.5) ANGLES ± .005

UNLESS OTHERWISE SPECIFIED,
ALL DIMENSIONS ARE GIVEN
IN INCHES, THIRD ANGLE PROJECTION.

DRAWN BY
JABO

MAT'L;

	SCALE
--	-------

NONE

DATE	11-11-98
------	----------

NYLON 6/6
HEAT STABILIZED AND
WEATHER RESISTANT

DRAWING NO.

SS-27185

DWG
A
SIZE

1	10-22-01	JABO		REMOVED PLST2H & 3H, PARTS OBSOLETE	27185	1				
REV	DATE	BY	CHK	DESCRIPTION	ECN	-	R	CUST	SUP	