



**Tripp Lite**  
1111 West 35th Street  
Chicago, IL 60609 USA  
Telephone: +(773) 869 1234  
E-mail: [saleshelp@tripplite.com](mailto:saleshelp@tripplite.com)

## Model #: SUPDM12

**Corded UPS Backplate Outlet Kit - Adds AC plug-in connection and AC output receptacles to SU6000RT3U and SU6000RT3UXR UPS for use with 208V UPS output voltage configurations**



### Highlights

- Converts Tripp Lite's hardwire SU6000RT3U UPS systems to one with AC plug and outlets
- For use with 208V mains and UPS output voltage configurations
- 10 ft. / 3m AC input power cable with NEMA L6-30P input plug
- 1 L6-30R, 2 L6-20R and 10 5-15/20R output receptacles
- Easy quick-connect wiring installs in minutes

### Description

Tripp Lite's SUPDM12 corded backplate kit converts Tripp Lite's hardwire SU6000RT3U or SU6000RT3UXR UPS system into one with AC plug and outlets. 10 ft./3m input line cord with L6-30P plug enables simple connection to 208V 30A mains power. Includes 1 L6-30R, 2 L6-20R and 10 5-15/20R output receptacles. Easy quick-connect wiring installs in minutes.

**VOLTAGE COMPATIBILITY NOTE** - SUPDM12 supports SU6000RT3U and SU6000RT3UXR applications configured for 208V nominal input voltage only (See SUPDM13 for 240V input voltage configurations).

#### Applications

- Ideal for 208V applications calling for Tripp Lite's SU6000RT3U and SU6000RT3UXR UPS systems where plug-in AC input and output connections are required

### Features

- Converts Tripp Lite's hardwire SU6000RT3U or SU6000RT3UXR UPS system to one with an AC plug and outlets
- 10 ft./3m AC line cord with L6-30P input plug-in connection
- Includes 1 L6-30R, 2 L6-20R and 10 5-15/20R output receptacles
- Easy quick-connect wiring installs in minutes

### Specifications

OVERVIEW	
Model Type	Outlet Kits
OUTPUT	
Output nominal voltage	Simultaneous 208 and 120V output
Overload protection	120V outlets are protected by 2 separate 20A branch rated circuit breakers
Outlet quantity / type	208V: 1 L6-30R, 2 L6-20R / 120V: 10 5-15/20R

<b>INPUT</b>	
Nominal Input Voltage(s) Supported	208V AC
UPS Input cord length (ft.)	10 ft. / 3m
UPS Input cord length (m)	3.05
Recommended Electrical Service	30A 208V
Input connection type	NEMA L6-30P input plug
Voltage compatibility (VAC)	208
<b>PHYSICAL</b>	
Shipping Dimensions (HWD/in)	5.5 x 9 x 14.25
Shipping Dimensions (HWD/cm)	14 x 22.9 x 36.2
Shipping weight (lbs)	6.6
Shipping weight (kg)	3
Unit Dimensions (HWD/in)	2.5 x 5 x 11
Unit Dimensions (HWD/cm)	6.4 x 12.7 x 28
Unit weight (lbs)	6
Unit weight (kg)	2.8
Material of construction	Steel
<b>WARRANTY</b>	
Product Warranty Period (Worldwide)	2-year limited warranty

Related Items

Optional Products

Related Model	Description	Qty.
<a href="#">PDUMH20</a>	Metered PDU / Power Distribution Unit- Safe, reliable power distribution with digital current meter	1
<a href="#">PDUMH20AT</a>	Metered PDU with ATS - Power Distribution Unit with dual-input Auto Transfer Switching	1
<a href="#">PDUMH20ATNET</a>	Switched, Metered PDU with ATS - Power Distribution Unit with dual-input Auto Transfer Switching, individual outlet control and SNMP network interface	1
<a href="#">PDUMH30HVNET</a>	Switched, Metered PDU with Remote Monitoring - 2U Rackmount Power Distribution Unit for Networks with Individually Switchable Outlets, Current Metering, Remote Monitoring and Control	1
<a href="#">PDUMV20</a>	Metered PDU / Power Distribution Unit - Safe, reliable power distribution with digital current meter	1
<a href="#">PDUMV20HV</a>	Metered 0U Vertical Rack PDU - Metered Power Distribution Unit for Network Applications	1
<a href="#">PDUMV20HVNET</a>	Switched, Metered PDU with Remote Monitoring - 0U Vertical Rackmount Power Distribution Unit for Networks with Individually Switchable Outlets, Current Metering, Remote Monitoring and Control	1

<a href="#">PDUMV20NET</a>	Switched, Metered PDU with Remote Monitoring - 0U Vertical Rackmount Power Distribution Unit for Networks with Individually Switchable Outlets, Current Metering, Remote Monitoring and Control	1
<a href="#">PDUMV30HV</a>	Metered 0U Vertical Rack PDU - Metered Power Distribution Unit for Network Applications	1
<a href="#">PDUMV30HVNET</a>	Switched, Metered PDU with Remote Monitoring - 0U Vertical Rackmount Power Distribution Unit for Networks with Individually Switchable Outlets, Current Metering, Remote Monitoring and Control	1
<a href="#">PDUMV40</a>	Metered PDU / Power Distribution Unit - Safe, dual-circuit power distribution with current meters	1
<a href="#">PDUNV</a>	Basic PDU / Power Distribution Unit - Safe, reliable power distribution for critical networking equipment	1
<a href="#">PDUV20</a>	Safe, reliable power distribution for critical networking equipment	1
<a href="#">PDUV30HV</a>	Basic 0U Vertical Rack PDU - Power Distribution Unit for Network Applications	1
<a href="#">PDU1220</a>	Basic PDU / Power Distribution Unit - Safe, reliable power distribution for critical networking equipment	1
<a href="#">PDU1230</a>	Basic PDU / Power Distribution Unit - Safe, reliable power distribution for critical networking equipment	1
<a href="#">PDU40TDUAL</a>	Basic PDU / Power Distribution Unit - Safe, dual-circuit power distribution for critical networking equipment	1

More information, including related products, owner's manuals, and additional technical specifications, can be found online at [www.tripplite.com/en/products/model.cfm?txtModelID=2777](http://www.tripplite.com/en/products/model.cfm?txtModelID=2777).

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.