



CONTACT CONFIGURATION

▲ SWITCH FUNCTION		
POS. 1	POS. 2	POS. 3
<DN>	OFF	<DN>
2-3	OPEN	2-1

1. ALL DIMENSIONS IN MM [INCH]
2. GENERAL TOLERANCE: $X.X = \pm 0.4$
 $X.XX = \pm 0.25$
3. TERMINAL NUMBERS FOR REF ONLY.
4. CONTACT MATERIAL: GOLD
5. RATING: 0.4VA @ 20V AC OR DC UL, CUL,
VDE APPROVED
6. ELECTRIC LIFE: 40,000 MAKE-AND-BREAK CYCLES
AT FULL LOAD.
7. INSULATION RESISTANCE: 1,000 MEGA-OHM MIN.
8. DIELECTRIC STRENGTH: 1,000 V RMS @SEA LEVEL.
9. OPERATING TEMPERATURE: -30° C TO 85° C
10. ▲ DENOTES CRITICAL PARAMETER.

B	15152	CHANGED DIM. & UPDATED NOTES	8/5/05	PV
A	13215	RELEASED FOR PRODUCTION	6/13/03	AR
REV.	ECN No.	DESCRIPTION	DATE	CHKD

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED

E-SWITCH®				
TITLE				
300AWSP4J2WHTVS2RE				
SCALE	DATE	DR	DWG	REV
2:1	6/13/03	AR	T301407	B