Data Sheet

TRI-150R Adjustable Tripod

Product Overview

The TDK TRI-150R tripod is designed specifically for mounting antennas and video cameras in EMC test environments. The tripod is constructed of durable, non-conductive, commercial grade fiberglass and plastic that provide the necessary stability while allowing for portability.

The tripod mast easily adjusts from 100 cm to 150 cm in height, and supports equipment up to 45 kg. The sturdy, fixed-length fiberglass legs feature adjustable foot pads to accommodate uneven floor surfaces. Smooth-rolling caster wheels can also be specified. The legs fold inward for storage or transportation between test sites.

The tripod also features an integrated level to allow quick and accurate positioning.

The TRI-150R is available with a variety of antenna and video camera mount adapters to meet your requirements.

Application

Antenna or video camera mounting

Features

- 1/4 20 screw mount adapter (standard)
- Supports up to 45 kg (100 lbs.)
- Customer can specify either fixed rubber feet or smooth-rolling caster wheels
- Integrated level for accurate positioning
- Custom antenna mount adapters available



The TDK TRI-150R Tripod is specifically designed for EMC test environments and can support up to 45 kg.



The TDK TRI-150R's built-in level and independently adjustable feet simplify positioning on uneven surfaces. Fixed rubber feet or smooth-rolling caster wheels can be specified.





TRI-150R Adjustable Tripod

Mechanical Specifications

Dimensions:

Extended Height: 150 cm (59 in.)

Collapsed Height: 100 cm (39.4 in.)

Base Diameter: 100 cm (39.4 in.)

Weight: 11 kg (24 lbs.)

Construction: Fiberglass and plastic

Finish: Preventive water absorp-

tion seal

Ordering Information

Product: Tripod

Model Number: TRI-150R

Warranty: 1 year

To place an order or to learn more about the TDK products that best meet your needs, contact your TDK sales representative:

TDK RF Solutions Inc.

1101 Cypress Creek Rd. Cedar Park, Texas 78613 USA

Phone: 1-512-258-9478
Fax: 1-512-258-0740
E-mail: info@tdkrf.com

World Wide Web: <u>www.tdkrfsolutions.com</u>



www.tdkrfsolutions.com