

REV. BF

Technical drawing of a mechanical part. The drawing shows a cross-section of a part with two vertical pins. A dimension line indicates a distance of .0900 [2.287] from the bottom of the pins to the top of the part. Below the drawing, the text "IN PROCESS 1" is written.

Technical drawing of a mechanical part in process. The drawing shows a cross-section of a component with two vertical pins. Dimensions and tolerances are indicated:

- Overall width: $.0900$
- Pin diameter: $.005 \text{ MAX}$ [$.127$]
- Pin height: $.0900$

IN PROCESS 2

Technical drawing of a MOUNT STACKER BODY. The drawing shows a side view of the component with two vertical pins. A dimension line indicates a distance of .0900 [2.287] between the top of the lower pin and the top of the upper pin. The text 'MOUNT STACKER BODY' is at the top left, and 'IN PROCESS 4' is at the bottom right.

PROPRIETARY NOTE
THIS DOCUMENT CONTAINS INFORMATION
CONFIDENTIAL AND PROPRIETARY TO
SAMTEC INC. AND SHALL NOT BE
REPRODUCED OR TRANSFERRED TO
OTHER DOCUMENTS OR DISCLOSED TO
OTHERS OR USED FOR ANY PURPOSE
OTHER THAN THAT FOR WHICH IT WAS
OBTAINED WITHOUT THE EXPRESSED
WRITTEN CONSENT OF SAMTEC INC.

FIG 2

** -MW: METAL WASHER USING TMM BODY
(ONE PER POSITION)
(30 POS MAX)

DWG NO:
TW-XX-XX-X-X-XXX-XXX-XXX-XX
SHEET 3 OF 3

Figure 1 shows schematic diagrams of various interconnects. The top row displays four types: $-S$ (single pin), $-D$ (dual pin), $-T$ (triple pin), and $-Q$ (quad pin). The middle row shows two types: -5 ROW (5-pin row) and -6 ROW (6-pin row). The bottom row shows two types: $-T$ (triple pin) and $-Q$ (quad pin). Each diagram is a line drawing showing the pins and the interconnect body.

Technical drawing of the SQT-01-MW-T connector. The drawing includes a side view, a top view, and two detailed views of the connector's features.

Side View Dimensions:

- Overall width: $.010 \pm .003$ [$.25 \pm .08$]
- Angle: 2°
- Pin pitch: $.0890$ [2.261]

Top View Dimensions:

- Pin pitch: $.0890$ [2.261]

Callouts:

- SQT-01-MW-T
- (5 POS PER ROW MIN / 30 POS PER ROW MAX)

TW-XX-XX-X-X-XXX-XXX-XXX-XX
SHEET 3 OF 3