

## Axial Leaded Ceramic Capacitors

## UP050CH751J-A-BZ



## ■ Features

- Item Summary  
50V, 750pF,  $\pm 5\%$ , Axial
- Lifecycle Stage  
Mass Production
- Standard packaging quantity (minimum)  
Taping 3000pcs

## ■ Products characteristics table

|                                       |                        |
|---------------------------------------|------------------------|
| External Dimensions (EIA/JIS)         | Axial/Axial            |
| Rated Voltage (max)                   | 50V                    |
| Capacitance                           | 750pF                  |
| Capacitance Tolerance                 | $\pm 5\%$              |
| Resistance                            | 10,000 M $\Omega$ min. |
| Q (min)                               | 1000                   |
| Temperature Characteristics (EIA/JIS) | -/CH                   |
| Temperature Range (EIA/JIS)           | -/-25 to +85°C         |
| RoHS Compliance                       | Yes                    |
| Soldering Method                      | Wave                   |

## ■ External Dimensions

|   |           |
|---|-----------|
| L | 3.2mm -   |
| D | 2.2mm max |

2013.11.01

The data is reference only. Electrical characteristics vary depending on environment or measurement condition.  
 TAIYO YUDEN reserves the right to make change to the Date at any time without notice.  
 Before making final selection, please check product specification.