





CIRCUIT 4 POS.

NOTES:

1. ALL DIMENSIONS IN MM
2. GENERAL TOLERANCE: $X.X \pm 0.4$
 $X.XX \pm 0.25$
3. TERM. NOS. FOR REFERENCE ONLY.
4. CONTACT RATINGS: 25mA @24VDC. (Switch)
100mA @50VDC. (Carry)
5. CONTACT MATERIAL:
CONTACTS: (MOVABLE) Copper w/Gold Plate
TERMINALS: BRASS w/Gold Plate
6. INSULATION RESISTANCE:
100 Mega-OHMS min. @500VDC
7. CONTACT RESISTANCE:
50 MILLI-OHMS typical @2-4VDC @100mA
8. OPERATING TEMP.:
-40°C to +80°C
9. PACKAGE: IN DISPENSING TUBES
WITH ALL POLES IN THE "OFF" POSITION.

RECOMMENDED P.C.B. LAYOUT



E-SWITCH®				
TITLE				
KAJ04 LA GT				
SCALE		DATE	DR	DWG
2:1		6/14/02	CJB	W823124
REV				
B				

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED				
REV.	ECN No.	DESCRIPTION	DATE	CHKD
A	12226	RELEASED FOR PRODUCTION	6/14/02	CJB
B	12293	REVISED E-LOGD	7/11/02	CJB