



1. ALL DIMENSIONS IN MM
2. GENERAL TOLERANCE: $X.X = \pm 0.4$
 $XX.XX = \pm 0.25$
3. TERM. NOS. FOR REFERENCE ONLY.
4. CONTACT RATINGS: 25mA @24VDC. (Switch)
100mA @50VDC. (Carry)
5. CONTACT MATERIAL:
CONTACTS: (MOVABLE) Copper w/Gold Plate
TERMINALS: BRASS w/Gold Plate
6. INSULATION RESISTANCE;
100 Mega-ohms min. @500VDC
7. CONTACT RESISTANCE;
50 MILLI-OHMS typical @2-4VDC @100mA
8. OPERATING TEMP. ;
-40°C to +80°C
9. PACKAGE: IN DISPENSING TUBES
WITH ALL POLES IN THE "OFF" POSITION.



E-SWITCH®

				TITLE			
				KAJ12 LA GT			
REV.		ECN No.	DESCRIPTION	DATE	CHKD		
A		12227	RELEASED FOR PRODUCTION	6/14/02	CJB		
B		12293	REVISED E-LOGO	7/11/02	CJB		
THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED							
SCALE		DATE		DR	DWG	REV	
2:1		6/14/02		CJB	W823131	B	