


PEELABLE POLYIMIDE TAPE SEAL

PEELABLE POLYIMIDE TAPE SEAL



NOTES:

1. ALL DIMENSIONS IN MM
2. GENERAL TOLERANCE: $X.X = \pm 0.4$
 $X.XX = \pm 0.25$
3. TERM. NOS. FOR REFERENCE ONLY.
4. CONTACT RATINGS: 25ma @ 24VDC.
5. CONTACT MATERIAL:
CONTACTS: BRASS w/Gold Plate
TERMINALS: BRASS w/GOLD Plate
6. PACKAGED: DISPENSING TUBES
WITH ALL POLES IN THE "OFF" POSITION.
7. TAPE SEAL FOR FLUX WASH.
8. ▲ DESIGNATE MAJOR:



			TITLE	KAJ12 TG GT LOW PROFILE W/TAPE SEAL		
A	12277	RELEASED FOR PRODUCTION	7/1/02	CJB		A
REV.	ECN No.	DESCRIPTION	DATE	CHKD		
THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED						
		SCALE	DATE	DR	DWG	REV
		2:1	7/1/02	CJB	W825331	A