

Part Number . . . **XRN.M13.GLL.6GZ**



Size/Series XPN / XP

[Request a quote](#)

MECHANICAL DETAILS

Shell Style/Model	XR/Z*: Free socket, key (N) or keys (P, S and T), with cable collet and nut for fitting a bend relief
Keying	3 key (alpha=30, plug: male contacts, receptacle: female contacts)
Housing Material	
Cable Fixing	J : 5.3 - 6.5 mm
Variant	GZ : Gray collet nut for bend relief

	A	L
mm.	15.7	46.7
in.	0.62	1.84



PERFORMANCE DETAILS

Insert Configuration	M13 : 13 Low Voltage
Insulator	L: PEEK
Specifications	
Contact Type:	Solder
Max. Matings:	1000
Contact Dia.:	0.7 mm (0.028in)
Bucket Dia.:	0.8 mm (0.032in)
Max. Solid Conductor:	0.36 mm^2 (AWG 22)
Max. Stranded Conductor:	0.36 mm^2 (AWG 28)
R (max):	8.5 mOhm

OTHER CHARACTERISTICS

F ret (average):	130 N
Working temperature:	-50 deg C to + 170 deg C
IP Rating	50
Catalog	

[Copyright](#) [Privacy policy](#) [Product safety](#)

