

Part Number . . . **XRN.M22.GLL.6GZ**

Size/Series XPN / XP

[Request a quote](#)

MECHANICAL DETAILS

Shell Style/Model XR/Z*: Free socket, key (N) or keys (P, S and T), with cable collet and nut for fitting a bend relief



Keying 3 key (alpha=30, plug: male contacts, receptacle: female contacts)

Housing Material

Cable Fixing J : 5.3 - 6.5 mm

Variant GZ : Gray collet nut for bend relief

	A	L
mm.	15.7	46.7
in.	0.62	1.84



PERFORMANCE DETAILS

Insert Configuration M22 : 22 Low Voltage

Insulator L: PEEK

Specifications

Contact Type: Solder

Max. Matings: 1000

Contact Dia.: 0.5 mm (0.0196in)

Bucket Dia.: 0.45 mm (0.0177in)

Max. Solid Conductor: 0.12 mm^2 (AWG 28)

Max. Stranded Conductor: 0.12 mm^2 (AWG 28)

R (max): 8.5 mOhm

OTHER CHARACTERISTICS

F ret (average): 130 N

Working temperature: -50 deg C to + 170 deg C

IP Rating 50

Catalog

[Copyright](#) [Privacy policy](#) [Product safety](#)

