

**RoHS compliant**

## FEATURES

### 1. 4-channel (4 Form A) in a small SOP16-pin package

The device comes in a miniature SOP measuring (W)10.37 × (L)4.4 × (H)2.1mm (W).408×(L).173×(H).083inch

This contributes to space-saving of PC board.

### 2. Both low on-resistance (R type) and low capacitance (C type) available at excellent characteristics of CxR10

- R type: On resistance 0.8Ω (typ.) Output capacitance 13pF (typ.)
- C type: On resistance 9.7Ω (typ.) Output capacitance 1.0pF (typ.)

### 3. High-speed switching of 0.03ms (C type, typical turn on time)

### 4. Applicable for 4 Form A use, as well as 4 independent 1 Form A

## TYPICAL APPLICATIONS

### 1. Measuring and testing equipment

IC tester, Liquid crystal driver tester, Semiconductor performance tester, Bare board tester, In-circuit tester, Function tester, etc.

### 2. Telecommunication and broadcasting equipment

### 3. Medical equipment

Ultrasonic wave diagnostic machine

### 4. Multi-point recorder

Warping, Thermo couple, etc.

## TYPES

| New            | Type                       | Output rating*1 |              | Package   | Part No.*2         |  |   | Packing quantity   |               |  |
|----------------|----------------------------|-----------------|--------------|-----------|--------------------|--|---|--|---------------|--|
|                |                            | Load voltage    | Load current |           | Tube packing style | Tape and reel packing style              |   | Tube   | Tape and reel |  |
|                |                            |                 |              |           |                    | Picked from the 1/2/3/4/5/6/7/8-pin side | Picked from the 9/10/11/12/13/14/15/16-pin side |  |               |  |
| AC/DC dual use | Low on-resistance (R type) | 40V             | 0.16A        | SOP16-pin | AQS221R2S          | AQS221R2SX                               | AQS221R2SZ                                      | 1 tube contains:<br>50 pcs.<br>1 batch contains:<br>1,000 pcs. | 1,000 pcs.    |  |
|                | Low capacitance (C type)   | 40V             | 0.06A        |           | AQS221N2S          | AQS221N2SX                               | AQS221N2SZ                                      |  |               |  |

Notes: \*1 Indicate the peak AC and DC values.

\*2 The packing style indicator "X" or "Z" is not marked on the device.

## RATING

### 1. Absolute maximum ratings (Ambient temperature: 25°C 77°F)


| Item                    |                         | Symbol            | AQS221R2S (R type)              |        | AQS221N2S (C type)                 |                                      | Remarks |
|-------------------------|-------------------------|-------------------|---------------------------------|--------|------------------------------------|--------------------------------------|---------|
| Input                   | LED forward current     | I <sub>F</sub>    | 50 mA                           |        |                                    |                                      |         |
|                         | LED reverse voltage     | V <sub>R</sub>    | 5 V                             |        |                                    |                                      |         |
|                         | Peak forward current    | I <sub>FP</sub>   | 1 A                             |        | f = 100 Hz, Duty factor = 0.1%     |                                      |         |
|                         | Power dissipation       | P <sub>in</sub>   | 75 mW                           |        |                                    |                                      |         |
| Output                  | Load voltage (peak AC)  | V <sub>L</sub>    | 40 V                            |        |                                    |                                      |         |
|                         | Continuous load current | I <sub>L</sub>    | 0.16 A                          | 0.06 A |                                    | Peak AC, DC                          |         |
|                         | Peak load current       | I <sub>peak</sub> | 0.2 A                           | 0.12 A |                                    | 100 ms (1 shot), V <sub>L</sub> = DC |         |
|                         | Power dissipation       | P <sub>out</sub>  | 600 mW                          |        |                                    |                                      |         |
| Total power dissipation |                         | P <sub>T</sub>    | 650 mW                          |        |                                    |                                      |         |
| I/O isolation voltage   |                         | V <sub>iso</sub>  | 500 V AC                        |        |                                    |                                      |         |
| Temperature limits      | Operating               | T <sub>opr</sub>  | −40°C to +85°C −40°F to +185°F  |        | Non-condensing at low temperatures |                                      |         |
|                         | Storage                 | T <sub>stg</sub>  | −40°C to +100°C −40°F to +212°F |        |                                    |                                      |         |

# RF SOP 4 Form A CxR10 (AQS221O2S)

2. Electrical characteristics (Ambient temperature: 25°C 77°F)

|                          | Item                             | Symbol     | AQS221R2S (R type)                       | AQS221N2S (C type) | Condition  |
|--------------------------|----------------------------------|------------|--|--------------------|--|
| Input                    | LED operate current              | $I_{Fon}$  | 0.5 mA                                   | 0.9 mA             | $I_L = \text{Max.}$  |
|                          |                                  |            | 3.0 mA                                   |                    |  |
|                          | LED turn off current             | $I_{Foff}$ | 0.1 mA                                   |                    | $I_L = \text{Max.}$  |
|                          |                                  |            | 0.4 mA                                   | 0.85 mA            |  |
| Output                   | LED dropout voltage              | $V_F$      | 1.25 V (1.14 V at $I_F = 5 \text{ mA}$ ) |                    | $I_F = 50 \text{ mA}$  |
|                          |                                  |            | 1.5 V                                    |                    |  |
|                          | On resistance                    | $R_{on}$   | 0.8Ω                                     | 9.5Ω               | $I_F = 5 \text{ mA}$<br>$I_L = \text{Max.}$<br>Within 1 s on time  |
|                          |                                  |            | 1.25Ω                                    | 12.5Ω              |  |
| Transfer characteristics | Output capacitance               | $C_{out}$  | 13.0 pF                                  | 1.0 pF             | $I_F = 0 \text{ mA}$<br>$V_B = 0 \text{ V}$<br>$f = 1 \text{ MHz}$                                       |
|                          |                                  |            | 18.0 pF                                  | 1.5 pF             |  |
|                          | Off state leakage current        | $I_{Leak}$ | 0.03 nA                                  | 0.01 nA            | $I_F = 0 \text{ mA}$<br>$V_L = \text{Max.}$  |
|                          |                                  |            | 10 nA                                    |                    |  |
|                          | Turn on time*                    | $T_{on}$   | 0.15 ms                                  | 0.03 ms            | $I_F = 5 \text{ mA}$<br>$V_L = 10\text{V}$<br>$R_L = 62.5\Omega$ (R type),<br>$R_L = 500\Omega$ (C type) |
|                          |                                  |            | 0.5 ms                                   | 0.2 ms             |  |
|                          | Turn off time*                   | $T_{off}$  | 0.06 ms                                  | 0.03 ms            | $I_F = 5 \text{ mA}$<br>$V_L = 10\text{V}$<br>$R_L = 62.5\Omega$ (R type),<br>$R_L = 500\Omega$ (C type) |
|                          |                                  |            | 0.2 ms                                   |                    |  |
|                          | I/O capacitance                  | $C_{iso}$  | 0.8 pF                                   |                    | $f = 1 \text{ MHz}$<br>$V_B = 0 \text{ V}$   |
|                          |                                  |            | 1.5 pF                                   |                    |  |
|                          | Initial I/O isolation resistance | $R_{iso}$  | 1,000 MΩ                                 |                    | 500 V DC   |

\*Turn on/Turn off time



## RECOMMENDED OPERATING CONDITIONS

Please obey the following conditions to ensure proper device operation and resetting.

| Item              | Symbol | Recommended value | Unit |
|-------------------|--------|-------------------|------|
| Input LED current | $I_F$  | 5                 | mA   |

## ■ For Dimensions.

## ■ For Schematic and Wiring Diagrams.

## ■ For Cautions for Use.

■ These products are not designed for automotive use.


If you are considering to use these products for automotive applications, please contact your local Panasonic Corporation technical representative.

For more information.

## REFERENCE DATA


### 1. Load current vs. ambient temperature characteristics

Allowable ambient temperature:  $-40^{\circ}\text{C}$  to  $+85^{\circ}\text{C}$   
 $-40^{\circ}\text{F}$  to  $+185^{\circ}\text{F}$




### 2. Load current vs. load voltage characteristics

Ambient temperature:  $25^{\circ}\text{C}$   $47^{\circ}\text{F}$




### 3. On resistance vs. ambient temperature characteristics

LED current: 5 mA; Load voltage: 10 V (DC); Continuous load current: 160 mA (DC) R type/ 60 mA (DC) C type




### 4. Turn on time vs. ambient temperature characteristics

LED current: 5 mA; Load voltage: 10 V (DC); Continuous load current: 160 mA (DC) R type/ 20 mA (DC) C type




### 5. Turn off time vs. ambient temperature characteristics

LED current: 5 mA; Load voltage: 10 V (DC); Continuous load current: 160 mA (DC) R type/ 20 mA (DC) C type




### 6. LED operate current vs. ambient temperature characteristics

Load voltage: 10 V (DC); Continuous load current: 160 mA (DC) R type/ 60 mA (DC) C type




### 7. LED turn off current vs. ambient temperature characteristics

Load voltage: 10 V (DC); Continuous load current: 160 mA (DC) R type/ 60 mA (DC) C type




### 8. LED dropout voltage vs. ambient temperature characteristics

LED current: 5 to 50 mA



### 9. Current vs. voltage characteristics of output at MOS portion


Ambient temperature:  $25^{\circ}\text{C}$   $77^{\circ}\text{F}$



# RF SOP 4 Form A CxR10 (AQS221O2S)


## 10. Off state leakage current vs. load voltage characteristics

Ambient temperature: 25°C 77°F




## 11. Turn on time vs. LED forward current characteristics

Load voltage: 10 V (DC);  
Continuous load current: 160 mA (DC) R type/  
20 mA (DC) C type  
Ambient temperature: 25°C 77°F




## 12. Turn off time vs. LED forward current characteristics

Load voltage: 10 V (DC);  
Continuous load current: 160 mA (DC) R type/  
20 mA (DC) C type  
Ambient temperature: 25°C 77°F




## 13. Output capacitance vs. applied voltage characteristics

Frequency: 1 MHz, 30 mVrms;  
Ambient temperature: 25°C 77°F



## 14. Isolation vs. frequency characteristics (50Ω impedance)

Ambient temperature: 25°C 77°F



## 15. Insertion loss vs. frequency characteristics (50Ω impedance)

Ambient temperature: 25°C 77°F

