

MICRO SWITCH
a Honeywell Division

FED. MFG. CODE 91929

SWITCH-ENCLOSED

CATALOG LISTING

BAFI-2RQN8-RH

CATALOG LISTING
BAFI-2RQN8-RH

ISSUE
10

REVISIONS
A CO-73287M
6JW
16 MAY 95

FORMTEK
DRAWN
6JW

REPLACES

RELEASE NO. SR-3592

CHECK


CHECK

25 MAY 95

JJA

CHECK

16 MAY 95



GASKET TYPE SEAL BETWEEN COVER AND HOUSING.

REF.
8-32 UNC X .562 PAN HEAD
SCREWS AND SPRING WASHERS
RETAINED.

.656 DIA. X .187 WIDE CORROSION-
RESISTANT STEEL ROLLER.

ROLLER PLUNGER ASSEMBLY MAY BE
SET AT ANY POSITION AROUND AXIS OF PLUNGER.

1/2-14 N.P.T. THREAD

.625 ±.010
.58 DIA.
.812 ±.010

(3) .265 DIA. HOLE


.25 R.

NOTE

- 1 - 8-32 UNC X (.219) BINDER HEAD, COMBINATION, TERMINAL SCREWS AND CUP WASHERS
- 2 - IT IS ESSENTIAL TO PREVENT ENTRANCE OF HARMFUL AGENTS THRU THE CONDUIT OPENINGS TO OBTAIN FULL BENEFITS OF THE WATERPROOF CONSTRUCTION PROVIDED IN THIS UNIT

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.

THIRD ANGLE PROJECTION



CHARACTERISTICS

OPERATING FORCE ----- 8 LBS. MAX.

RELEASE FORCE ----- 2 LBS. MIN.

DIFFERENTIAL TRAVEL ----- .0075 MAX.

OVERTRAVEL ----- .187 MIN.

SWITCH-BASIC REPLACEMENT --- BA-2R708-P7

ELECTRICAL DATA

CONTACT ARRANGEMENT
S P D T

BREAK DISTANCE
.020 MIN.

L23 20A 125, 250 OR 480 VAC
10A 125 VAC "L"
1HP 125 VAC, 2HP 250 VAC
1/2A 125 VDC, 1/4A 250 VDC



SCALE FULL

**DO NOT
SCALE PRINT**

**UNLESS OTHERWISE SPECIFIED
TOLERANCES ARE**

ONE PLACE (.0) ±.030

TWO PLACE (.00) ±.015

THREE PLACE (.000) ±.005

ANGLES ±

WEIGHT