

FED. MFR. CODE 91929

CATALOG LISTING

BAF1-3RN2X-LH

FORMTEK



THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF MINNEAPOLIS-HONEYWELL REGULATOR CO. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.			
CHARACTERISTICS		ELECTRICAL DATA	
OPERATING FORCE----- 1 1/2 LB MAX OVERTRAVEL----- .250 MIN PRETRAVEL----- .219 MAX RESET CHARACTERISTICS OPERATING FORCE----- 1 3/4 LB MAX OVERTRAVEL----- .219 MIN SWITCH-BASIC REPLACEMENT---BA-3RX717		CONTACT ARRANGEMENT SINGLE POLE DOUBLE THROW MAINTAINED CONTACT L 224 20A 125, <u>250</u> OR 480VAC 1HP 125VAC, 2HP <u>250</u> VAC 1/2A 125VDG, 1/4A 250VDG  	
		SCALE FULL	
		DO NOT SCALE PRINT	
		UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ARE: ONE PLACE (.0) ±.030 TWO PLACE (.00) ±.015 THREE PLACE (.000) ±.005 ANGLES ±	
		WEIGHT	