

**MICRO SWITCH**FREEPORT, ILLINOIS, U.S.A.
A DIVISION OF HONEYWELL

FED. MFG. CODE 91929

SWITCH - BASIC

CATALOG LISTING

BZ-2R-A2

AGM2000 / JG-05660

BZ-2R-A2

PAGE 1 OF 1

MDRAWING
NUMBER

13

ISSUE

REPLACES

RELEASE NO.

CHECK

REVISIONS

A CO17410

G C H
12 APRIL 63

B CO31092

C CO-73287-B
OCT 72D H O
17 MAY 93

D CO-77589

K D R
29 MAR 94

E CO93346

D L T
1 SEP 98

F 0015138

SPK
29 AUG 05

29 AUG 05

RJ

CHECK

22 APR 63

CHECK

63

G C H 12 APRIL 63

FORMTEK

FO-50376

DRAWN

3X 6-32 UNC X (219) BINDING
HEAD COMBINATION TERMINAL
SCREW AND CUPWASHER

NOTE

△ - MOUNTING HOLES WILL ACCEPT PINS OR SCREWS
OF .139 MAX DIA ON 1.000 ± .002 CENTERS

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF MINNEAPOLIS-HONEYWELL REGULATOR CO. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.

CHARACTERISTICS

OPERATING FORCE ----- 9 - 13 OZ

RELEASE FORCE ----- 4 OZ MIN

DIFFERENTIAL TRAVEL ---- .0004 - .0020

OVERTRAVEL ----- .005 MIN

ELECTRICAL DATA

CONTACT ARRANGEMENT

S P D T

-L74- 15A-125, 250 OR 480 VAC, 2A-600 VAC
1/8HP-125 VAC; 1/4HP-250 VAC
1/2A-125 VDC; 1/4A-250 VDC-L288-
-L306-
-L315-EN05
EC

16A 250V ~ T85 5E4

SCALE FULL

DO NOT SCALE PRINT

UNLESS OTHERWISE
NOTED

DIMENSIONS ARE IN INCHES

TOLERANCES ARE:

ONE PLACE (.0) ±.030
TWO PLACE (.00) ±.015
THREE PLACE (.000) ±.005
ANGLES ±

WEIGHT .063 LB