

MICRO SWITCH

FREEPORT ILLINOIS, U.S.A
A DIVISION OF HONEYWELL INC.
FED. MFG. CODE 91929

SWITCH — BASIC

CATALOG LISTING

BZ-2RD39-A2

BZ-2RD39-A2

PAGE 1 OF 1

M

DRAWING
NUMBER

3
ISSUE

X89201-BZ

REPLACES PR-16649

CHECK

REVISIONS

A CO-73287-J
J A L
22 NOV 93
B C093346
DLT
8 SEP 98

CHECK

26 AUG '88

DAW


CHECK

J A P 24 AUG 88

FORMTEK

FO-52848-B

DRAWN




NOTES

- 1 MOUNTING HOLES WILL ACCEPT PINS OR SCREWS OF .165 MAX DIA ON 1.000 ± .002 CENTERS

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.

THIRD ANGLE PROJECTION



CHARACTERISTICS

OPERATING FORCE — — — — — 9-13 OZ

RELEASE FORCE — — — — — 4 OZ MIN

DIFFERENTIAL TRAVEL — .0004—.0020

OVERTRAVEL — — — — — .060 MIN

ELECTRICAL DATA

CONTACT ARRANGEMENT
S P D T

L98 15A 125, 250 OR 480 VAC
1/8 HP 125 VAC, 1/4 HP 250 VAC
1/2A 125 VDC, 1/4A 250 VDC

L288
L299
L306
CE Ⓢ A Ⓢ

16A 250V ~ T85 5E4

SCALE FULL

DO NOT SCALE PRINT

UNLESS OTHERWISE SPECIFIED
TOLERANCES ARE

ONE PLACE (.0) ± .030
TWO PLACE (.00) ± .015
THREE PLACE (.000) ± .005
ANGLES ±

WEIGHT .064 LB