

MICRO SWITCH

FREEMONT ILLINOIS, U.S.A.
A DIVISION OF HONEYWELL
FED. MFG. CODE 91929

SWITCH - BASIC

BZ-2RW80331

BZ-2RW80331

PAGE 1 OF 1

M

DRAWING
NUMBER

6

ISSUE

REPLACES

RELEASE NO. PR-8635

CHECK

REVISIONS

A	0047585
	KAK
	12 MAY 80
B	0058037
	SMA
	1 OCT 85
C	0077591
	DAW
	22 JUN 94
D	0093346
	DLT
	14 SEP 98
E	0094212-C
	DLT
	17 SEP 99

CHECK

14 APR 80

CHECK

CHECK

80

CHECK

9


CHECK

FORMTEK

FO-52848-A

DRAWN

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.



CHARACTERISTICS	ELECTRICAL DATA	SCALE	FULL																														
OPERATING FORCE — — — 2 1/2 OZ MAX	CONTACT ARRANGEMENT S P D T	DO NOT SCALE PRINT																															
RELEASE FORCE — — — — 1/2 OZ MIN	UL LISTED-FILE E12252 CODE L96 15A-125, <u>250</u> OR 480 VAC 1/8 HP-125 VAC; 1/4 HP- <u>250</u> VAC 1/2 A-125 VDC; 1/4 A-250 VDC	TOLERANCES APPLY TO DESIGN UNITS. CONVERSIONS ARE ONLY FOR REFERENCE. UNLESS NOTED, TOLERANCES ARE:																															
DIFFERENTIAL TRAVEL — — — .007-.050	L288 L299 L306	<table><tr><td>DIM. in</td><td>TOL. mm/in</td><td>DIM. in</td><td>TOL. mm/in</td></tr><tr><td>NO PLACES</td><td>X</td><td>1/16</td><td>X</td></tr><tr><td>ONE PLACE</td><td>X, X</td><td>0.4/0.16</td><td>X, X</td></tr><tr><td>TWO PLACES</td><td>X, XX</td><td>0.15/1.06</td><td>X, XX</td></tr><tr><td>THREE PLACES</td><td>X, XXX</td><td></td><td>X, XXX</td></tr><tr><td>ANGLES</td><td></td><td></td><td></td></tr></table>	DIM. in	TOL. mm/in	DIM. in	TOL. mm/in	NO PLACES	X	1/16	X	ONE PLACE	X, X	0.4/0.16	X, X	TWO PLACES	X, XX	0.15/1.06	X, XX	THREE PLACES	X, XXX		X, XXX	ANGLES				<table><tr><td>DESIGN UNITS</td><td>SI METRIC</td><td>IS CUSTOM</td></tr><tr><td>☐</td><td>☒</td><td>☒</td></tr></table>	DESIGN UNITS	SI METRIC	IS CUSTOM	☐	☒	☒
DIM. in	TOL. mm/in	DIM. in	TOL. mm/in																														
NO PLACES	X	1/16	X																														
ONE PLACE	X, X	0.4/0.16	X, X																														
TWO PLACES	X, XX	0.15/1.06	X, XX																														
THREE PLACES	X, XXX		X, XXX																														
ANGLES																																	
DESIGN UNITS	SI METRIC	IS CUSTOM																															
☐	☒	☒																															
OVERTRAVEL — — — — — .219 MIN	L288 L299 L306 16A 250V ~ T85 5E4	WEIGHT	.060 LB																														

NOTE

⚠ MOUNTING HOLES WILL ACCEPT PINS OR SCREWS OF .139 MAX DIA ON 1.000 ± .002 CENTERS

