



6-32 UNC X .219 REF BINDING
 HEAD TERMINAL SCREW
 AND LOCKWASHER (SEMS)(3)

NOTE
 MOUNTING HOLES WILL ACCEPT PINS OR SCREWS
 OF .139 MAX DIA ON 1.000 ± .002 CENTERS

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF MINNEAPOLIS-HONEYWELL REGULATOR CO. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.

CHARACTERISTICS

OPERATING FORCE - - - - 2 OZ MAX
 RELEASE FORCE - - - 1/4 OZ MIN
 DIFFERENTIAL TRAVEL - - .004 - .026
 OVERTRAVEL - - - - .141 MIN

ELECTRICAL DATA

CONTACT ARRANGEMENT
 S P D T
 -L96- 15 A - 125, 250, OR 480 VAC
 1/2 A - 125 VDC; 1/4 A - 250 VDC
 1/8 HP - 125 VAC, 1/4 HP - 250 VAC

-L288- CE EN 05 SP RU
 -L315-
 -L306-

16A 250V ~ T85 5E4

SCALE FULL

DO NOT SCALE PRINT

UNLESS OTHERWISE NOTED
 DIMENSIONS ARE IN INCHES
TOLERANCES ARE:
 ONE PLACE (.0) ± .030
 TWO PLACE (.00) ± .015
 THREE PLACE (.000) ± .005
 ANGLES ±

WEIGHT .073 LB

FORMTEK
 FO-50376
 DRAWN M B F 29 JAN 68
 CHECK LSD 31 JAN 68
 CHECK KRB 08DEC05
 REVISIONS
 A PR -760
 D L F
 16 JUN 69
 B CO
 68751-D
 JMB
 18 JUL 91
 C CO
 77589
 TSM
 29 MAR 94
 D CO93346
 DLT
 17 SEP 98
 E 0017579
 KRB
 08DEC05
 REPLACES RELEASE NO. PR - 760
 X 39435-BZ
M BZ-2RW84375T
 PAGE 1 OF 1
 DRAWING NUMBER
 ISSUE 6
 CHECK 08DEC05
 CHECK RJ
 CHECK 08DEC05