


MICRO SWITCH

FREEPORT ILLINOIS, U.S.A
A DIVISION OF HONEYWELL
FED. MFG. CODE 91929

SWITCH-BASIC

CATALOG LISTING

BZ-3RW822158-A46



NOTE -
▲ - MOUNTING HOLES WILL ACCEPT PINS OR SCREWS
OF .139 MAX DIA ON $1.000 \pm .002$ CENTERS

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH. A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.

THIRD ANGLE PROJECTION

CHARACTERISTICS

OPERATING FORCE --- 6 1/2 OZ MAX
RELEASE FORCE --- 1 1/2 OZ MIN
DIFFERENTIAL TRAVEL --- .007 - .030
OVERTRAVEL --- .094 MIN

ELECTRICAL DATA

CONTACT ARRANGEMENT
S P D T

10A 125, 250 OR 480 VAC
1/2 A 125 VDC, 1/4 A 250 VDC

UL CE L288

SCALE FULL

DO NOT SCALE PRINT

TOLERANCES

APPLY TO DESIGN UNITS. CONVERSIONS ARE ONLY FOR
REFERENCE. UNLESS NOTED, TOLERANCES ARE ±

DIM.	TOL.	DIM.	TOL.
mm	mm/in	in	mm/in
NO PLACES	X	1/04	X X
ONE PLACE	X, X	0.4/.016	X X
TWO PLACES	X, XX	0.15/.006	X XX
THREE PLACES	X, XXX	0.13/.005	X XXX
ANGLES			

DESIGN UNITS ☐ SI METRIC ☐ US CUSTOMARY

WEIGHT .076 LB

M BZ-3RW822158-A46

PAGE 1 OF 1

DRAWING
NUMBER

4

ISSUE

REPLACES X81348-BZ

RELEASE NO. PR-13967

CHECK

REVISIONS

A	070184	GJW	11 JAN 92
B	00-77588	KDR	29 MAR 94
C	0093346	DLT	14 AUG 98

CHECK

12 JUN 85

KAG

CHECK

12 JUN 85

KEW

FORMTEK

FO-52848-A

DRAWN