

MICRO SWITCH

FREEPORT ILLINOIS, U.S.A

A DIVISION OF HONEYWELL

FED. MFG. CODE 91929

SWITCH - BASIC

CATALOG LISTING

BZ-R7216 - P5

CATALOG LISTING
BZ-R7216 - P5
PAGE 1 OF 1

M

ISSUE
8

REPLACES

RELEASE NO. PR-4993

CHECK

REVISIONS

A	CO-39965	JJS	1 MAY 78
B	CO-44131	RJW	18 MAY 78
C	CO-73267-G	JAT	20 OCT 93
D	CO-75367B	KDR	3 MAR 94
E	CO-77863	GJW	1 MAY 96
F	CO93346	DLT	18 AUG 98
G	203225	CSL	7 JUN 01

CHECK

14 MAY 75

14 MAY 75

14 MAY 75

14 MAY 75

14 MAY 75

14 MAY 75

14 MAY 75

14 MAY 75

14 MAY 75

14 MAY 75

14 MAY 75


3X 8-32 UNC (.219) BINDING
HEAD COMBINATION TERMINAL
SCREW AND CUPWASHER

NOTES

- 1 MOUNTING HOLES WILL ACCEPT PINS OR SCREWS
OF .139 MAX DIA ON $1.000 \pm .002$ CENTERS
- 2 - CONTACT MATERIAL - GOLD ALLOY

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.

THIRD ANGLE PROJECTION



CHARACTERISTICS

OPERATING FORCE - - - - - 7-9 OZ

RELEASE FORCE - - - - - 4 OZ MIN

DIFFERENTIAL TRAVEL - .00015-.00035

OVERTRAVEL - - - - - .005 MIN

ELECTRICAL DATA

CONTACT ARRANGEMENT
S P D T

-L22

-L288

-L299

-L307

1A 125 VAC



1A 250 V $\sim$ T85 25E3

SCALE FULL

DO NOT SCALE PRINT

TOLERANCES

APPLY TO DESIGN UNITS. CONVERSIONS ARE ONLY FOR
REFERENCE. UNLESS NOTED, TOLERANCES ARE 2

NO PLACES	DIM. mm	TOL. mm/in	DIM. in	TOL. mm/in
ONE PLACE	X	1/64	X.X	0.01/0.001
TWO PLACES	X.X	0.01/0.001	X.XX	0.001/0.0001
THREE PLACES	X.XX	0.001/0.0001	X.XXX	0.0001/0.00001

DESIGN UNITS ☐ SI METRIC

US CUSTOMARY ☒

WEIGHT .075 LB

FO-52848-A

DRAWN

CHECK

14 MAY 75

14 MAY 75

14 MAY 75

14 MAY 75

14 MAY 75

D	B	W	I	3	MAY	75	CHECK
---	---	---	---	---	-----	----	-------