

8

7

6

5

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

ALL RIGHTS RESERVED.

LOCAD

DIST0

REV

DESCRIPTION

DATE

DW

APVD

AE1

REVISED PER ECO-11-004820

11MAR11

RK

HMR

1. RECEPTACLE ACCEPTS A .008-.014 THICK I.C. LEAD.

2. TUBE LOADED FOR AUTOMATIC INSERTION.

3 TWO .000030 MIN THK. GOLD STRIPES IN CONTACT AREA WITH TIN-LEAD (93/7) ON CONTACT LEGS, BALANCE OF CONTACT NICKEL PLATED.

4 TWO .000015 MIN THK. GOLD STRIPES IN CONTACT AREA WITH TIN-LEAD (93/7) ON CONTACT LEGS, BALANCE OF CONTACT NICKEL PLATED.

CIRCUIT CAVITY NO. 1

.052 TYP

.395

A

AMP

A

.023±.002 TYP

.048

.100±.008 TYP

.394

.321 MIN

.210 MAX

.128±.007

.150±.004

.300 REF

.015 TYP

.310

.054 REF

.175 MAX

.030

I.C. D.I.P.

LEAD CONTACT AREA

P.C. BOARD SURFACE

SECTION A-A

SCALE 10:1

.300

.100 TYP

Ø.036±.003 TYP

Ø.009

RECOMMENDED MOUNTING HOLE PATTERN

SCALE 4:1

OBSOLETE

TINNED

PHOS.BRZ. .006 THK

GLASS-FILLED THERMOPLASTIC, 94V-O, BLACK

2-640463-5

SUPERSEDED BY 390261-2

4

TINNED

PHOS.BRZ. .006 THK

GLASS-FILLED THERMOPLASTIC, 94V-O, BLACK

2-640463-4

SUPERSEDED BY 390261-2

4

TINNED

PHOS.BRZ. .006 THK

GLASS-FILLED THERMOPLASTIC, 94V-O, BLACK

2-640463-3

SUPERSEDED BY 390261-2

4

TINNED

BE.CU. .006 THK

GLASS-FILLED THERMOPLASTIC, 94V-O, BLACK

2-640463-2

SUPERSEDED BY 390261-2

4

TINNED

BE.CU. .006 THK

GLASS-FILLED THERMOPLASTIC, 94V-O, BLACK

2-640463-1

CONTACT FINISH

CONTACT MAT'L

HOUSING MATERIAL

PART NO.

THIS DRAWING IS A CONTROLLED DOCUMENT.

DW

M. CYRUS

2-20-87

CHK

R. MILLER

2-20-87

APVD

J. LAMBERT

2-28-87

NAME

SOCKET ASSY, DIP, 8 POS, DIPLOMATE DL

SIZE

CAGE CODE

DRAWING NO

RESTRICTED TO

A1

00779

640463

—

CUSTOMER DRAWING

SCALE

5:1

SHEET

1

OF

1

REV

AE1