

Part Number: C2065A

Revision Level: 02

Date: March 7, 2006

## 1C 16 26/30 TC PVC INS

## HOOK-UP WIRE

### A. CONSTRUCTION

- |    |  | <u>DIAMETERS</u>  |
|----|--|-------------------|
| 1) | CONDUCTOR: #16 AWG 26/30 Tinned Copper   | 0.060" nom.       |
| 2) | INSULATION: 0.016" Wall Polyvinyl Chloride   | 0.092" +/- 0.005" |
| 3) | PRINT LEGEND: <b>CAROL A 16 AWG RU AWM 80C VW-1 E18621-8 --- CSA LL69381 TR64 90C --<br/>- MADE IN USA</b> |                   |

### B. INDUSTRY APPROVALS

UL Subject 758

AWM Style 1007, 1569

CSA International

Type TR64

### C. ELECTRICAL PROPERTIES

- |    |                                   |                                |
|----|-----------------------------------|--------------------------------|
| 1) | TEMPERATURE:                      | 80 C                           |
| 2) | SUGGESTED WORKING VOLTAGE (Vrms): | 300Vrms                        |
| 3) | CONDUCTOR D.C. RESISTANCE:        | 4.39 Ohms/1000 ft. nom. @ 20 C |

Note: Data are subject to change without notice. Contact your Customer Service representative for latest information.