

251/253 Series, PICO® II, Very Fast-Acting Fuse



Description

The PICO® II Very Fast-Acting Fuse is designed to meet an extensive array of performance characteristics in a space-saving subminiature package.

Features






- Very fast-acting
- Small size
- Wide current rating range (62mA- 15A)
- RoHS compliant (251 Series only)
- Halogen-free available (251 Series only)
- Wide operating temperature range
- Low temperature derating

Applications


Secondary protection for space constrained applications

- Flat-panel display TV
- LCD monitor
- LCD backlight inverter
- Office machines
- Power supply
- Audio/Video system
- Lighting system
- Medical equipment

Agency Approvals for 251 Series

Agency	Agency File Number	Ampere Range
	E10480	62mA - 15A
	LR 29862	62mA - 15A
	JET 1896-31007-1001	1A - 5A
	J50158379	500mA - 10A
	2009010207366577 - 500mA to 5A	500mA, 1A, 2A, 2.5A, 3A, 4A, 5A






Agency Approvals for 253 Series

Agency	Agency File Number	Ampere Range
	FM10	62mA - 15A


Electrical Characteristics for Series

% of Ampere Rating	Ampere Rating	Opening Time
100%	62mA - 15A	4 Hours, Min.
	62mA - 7A	1 Second, Max.
200%	10A	3 Seconds, Max.
	12 - 15A	10 Seconds, Max.
275%	500mA, 1A, 2A, 2.5A, 3A, 4A, 5A, 7A, 10A	300 msec., Max.
400%	500mA, 1A, 2A, 2.5A, 3A, 4A, 5A, 7A, 10A	30 msec., Max.
1000%	500mA, 1A, 2A, 2.5A, 3A, 4A, 5A, 7A, 10A	4 msec., Max.

Electrical Specifications by Item for 251 Series


Ampere Rating (A)	Amp Code	Ordering Number (Std.)	Ordering Number (Mil.)	Max Voltage Rating (V)	Interrupting Rating	Nominal Cold Resistance (Ohms)	Nominal Melting I ² t (A ² sec)	Nom Voltage Drop (V)	Agency Approvals				
													
.062	.062	251.062	253.062	125	300 A @ rated voltage DC	7.000	0.000113	1.4	x	x			
.125	.125	251.125	253.125	125		1.700	0.00174	0.285	x	x			
.250	.250	251.250	253.250	125		0.665	0.0116	0.24	x	x			
.375	.375	251.375	253.375	125		0.395	0.0296	0.215	x	x			
.500	.500	251.500	253.500	125		0.280	0.0598	0.2165	x	x		x	x
.630	.630	251.630		125		0.205	0.094	0.188	x	x			
.750	.750	251.750	253.750	125	0.175	0.153	0.176	x	x		x		
1.00	001.	251001.	253001.	125	50 A @ rated voltage AC	0.128	0.256	0.194	x	x	x	x	x
1.25	1.25	2511.25		125		0.100	0.390	0.2	x	x	x		
1.50	01.5	25101.5	25301.5	125	For CCC 7A: 70 A @ rated voltage AC	0.0823	0.587	0.21	x	x	x	x	
2.00	002.	251002.	253002.	125		0.0473	0.405	0.141	x	x	x	x	x
2.50	02.5	25102.5		125		0.0360	0.721	0.132	x	x	x	x	x
3.00	003.	251003.	253003.	125	For CCC 10A: 100 A @ rated voltage AC	0.0290	1.19	0.131	x	x	x	x	x
3.50	03.5	25103.5		125		0.0240	1.58	0.1205	x	x	x	x	
4.00	004.	251004.	253004.	125		0.0204	2.45	0.114	x	x	x	x	x
5.00	005.	251005.	253005.	125		0.0155	4.14	0.11	x	x	x	x	x
7.00	007.	251007.	253007.	125		0.0105	10.4	0.102	x	x		x	
10.0	010.	251010.	253010.	125		0.00705	25.5	0.1	x	x		x	
12.0	012.	251012.		32	0.0055	45.2	0.0878	x	x				
15.0	015.	251015.	253015.	32	0.00446	68.8	0.071	x	x				

Electrical Specifications by Item for 253 Series

Ampere Rating (A)	Amp Code	Ordering Number (Std.)	Ordering Number (Mil.)	Max Voltage Rating (V)	Interrupting Rating	Nominal Cold Resistance (Ohms)	Nominal Melting I ² t (A ² sec)	Nom Voltage Drop (V)	Agency Approvals
									
.062	.062	251.062	253.062	125	300 A @ rated voltage DC	7.000	0.000113	1.4	x
.125	.125	251.125	253.125	125		1.700	0.00174	0.285	x
.250	.250	251.250	253.250	125		0.665	0.0116	0.24	x
.375	.375	251.375	253.375	125		0.395	0.0296	0.215	x
.500	.500	251.500	253.500	125		0.280	0.0598	0.2165	x
.630	.630	251.630		125		0.205	0.094	0.188	
.750	.750	251.750	253.750	125	0.175	0.153	0.176	x	
1.00	001.	251001.	253001.	125	50 A @ rated voltage AC	0.128	0.256	0.194	x
1.25	1.25	2511.25		125		0.100	0.390	0.2	
1.50	01.5	25101.5	25301.5	125	For CCC 7A: 70 A @ rated voltage AC	0.0823	0.587	0.21	x
2.00	002.	251002.	253002.	125		0.0473	0.405	0.141	x
2.50	02.5	25102.5		125		0.0360	0.721	0.132	
3.00	003.	251003.	253003.	125	For CCC 10A: 100 A @ rated voltage AC	0.0290	1.19	0.131	x
3.50	03.5	25103.5		125		0.0240	1.58	0.1205	
4.00	004.	251004.	253004.	125		0.0204	2.45	0.114	x
5.00	005.	251005.	253005.	125		0.0155	4.14	0.11	x
7.00	007.	251007.	253007.	125		0.0105	10.4	0.102	x
10.0	010.	251010.	253010.	125		0.00705	25.5	0.1	x
12.0	012.	251012.		32	0.0055	45.2	0.0878		
15.0	015.	251015.	253015.	32	0.00446	68.8	0.071	x	

Note: Higher ampere ratings are available. Please contact Littelfuse Technical Support or your Littelfuse products representative for assistance.

Temperature Derating Curve



Note:

1. Derating depicted in this curve is in addition to the standard derating of 25% for continuous operation.

Soldering Parameters

Recommended Process Parameters:

Wave Parameter

Preheat:

(Depends on Flux Activation Temperature)

Temperature Minimum:

Temperature Maximum:

Preheat Time:

Solder Pot Temperature:

Solder Dwell Time:


Recommended Hand Soldering Parameters:

Solder Iron Temperature: 350° C +/- 5°C

Heating Time: 5 seconds max.

Note: These devices are not recommended for IR or Convection Reflow process

Average Time Current Curves




Product Characteristics


Materials	Encapsulated, Epoxy-Coated Body: Pure Tin-coated Copper wire leads
Solderability	MIL-STD-202, Method 208
Lead Pull Force	MIL-STD-202, Method 211, Test Condition A (will withstand a 7lbs. axial pull test)
Fuses To MIL SPEC	251/253 Series is available in FM10 on QPL for MIL-PRF-23419. To order, change 251 to 253

Operating Temperature	-55°C to +125°C
Shock	MIL-STD-202, Method 213, Test Condition I (100 G's peak for 6 msecs.)
Vibration	MIL-STD-202, Method 201 (10–55 Hz); Method 204, Test Condition C (55–2000 Hz at 10 G's Peak)
Moisture Resistance	MIL-STD-202, Method 106
Resistance to Soldering Heat	Withstands 60 seconds above 200°C and up to 260°C, maximum
Flammability Rating	UL 94V-0

Dimensions



Part Numbering System



Packaging

Packaging Option	Packaging Specification	Quantity & Packaging Code
*T1: 52.4mm (2.062") Tape and Reel	EIA 296	Please refer to available quantities above in "Part Numbering System"
**T3: 73mm (2.874") Tape and Reel	EIA 296	

The default lead length for both ammo pack and loose pack is T1 for 251 and is T3 for 253.

Notes: * T1 dimension is defined as the length of the component between the two tapes. The full component length is 62.7mm (2.468"). **T1 length is for 251 series only.**
 ** T3 dimension is defined as the length of the component between the two tapes. The full component length is 83.37mm (3.28"). **T3 length is for 253 series only.**