

5

4

3

2

1

受控 CONTROLLED DOCUMENT

编号
P/N

32-2098UL

版本
Rev

01

日期






Rel'd Date

May8,09

DRAWING NO.
32-2098UL

REVISIONS

REVISIONS					
01	OFFICIAL RELEASE				
	04-24-09	T	T	T	Thomas Chow 2009.05.04 P54311 +08'00'



NOTES:

1. ELECTRICAL SPECIFICATIONS

INSULATION RESISTANCE: 1000 MEGOHMS
WITHSTAND VOLTAGE: 1000V,AC/ MINUTE

2. MECHANICAL SPECIFICATIONS

CONTACT MATERIAL: PHOSPHOR BRONZE 0.3MM THICKNESS
CONTACT PLATING: 50 MICRO-INCH GOLD PLATE OVER 100
MICRO-INCH NICKEL PLATING


HOUSING MATERIAL: POLYCARBONATE
DURABILITY: 1000 CYCLES MIN
UL FLAMABILY RATING: 94-V0

3. ENVIRONMENTAL SPECIFICATIONS


TEMPERATURE RANGE: -40 °C TO +70 °C

4. FOR FLAT OVAL OR ROUND CABLE

5. FOR SOLID OR STRANDED WIRE APPLICATIONS



CONTACT



THIS DRAWING TO BE INTERPRETED
PER ANSI Y 14.5M - 1994

COMPANY CONFIDENTIAL

TOLERANCE UNLESS OTHERWISE SPECIFIED		DRAWN BY	DATE
		TERRY.W	04-24-09
DECIMALS	mm	CHECKED BY	DATE
X	± 0.5	TERRY.W	04-24-09
X.X	± 0.15	APPROVED BY	DATE
X.XX	± 0.10	THOMAS	04-24-09
ANGLES	± 0.5°	U/M: mm	
THIS DRAWING WAS PRODUCED BY COMPUTER, DO NOT SCALE DRAWING OR UPDATE MANUALLY.			

		Connectivity Solutions	
TITLE		RJ45 MOD PLUG SHIELDED,SOLID,U	
SHEET	DRAWING NO.	SIZE	
1 OF 1	32-2098UL	C	