


RED INDICATES ORIGINAL

DWG		DATA CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF TROMPETER ELECTRONICS, INC. AND SHALL NOT BE REPRODUCED, COPIED, EITHER WHOLLY OR IN PART, WITHOUT THE WRITTEN PERMISSION OF TROMPETER ELECTRONICS, INC.	REVISIONS		105-0376	SH 1C
REV	ECO	DESCRIPTION	DWN	APPROVED	DATE	
1	12581	ADDED: -15, -16 & -17; SH 2 REDRAWN, SEE ECO	DKC	LHM	7/9/83	


TABLE 1	
DASH NO	DESCRIPTION
-1	TERM (NO CHAIN)
-2	TERM WITH 2.5 BRASS CHAIN
-3	TERM WITH 2.5 NYLON CHAIN
-4	TERM WITH 3.0 BRASS CHAIN
-5	TERM WITH 3.0 NYLON CHAIN
-6	TERM WITH 6.0 BRASS CHAIN
-7	TERM WITH 6.0 NYLON CHAIN
-8	TERM WITH 4.0 BRASS CHAIN
-9	TERM WITH 4.0 NYLON CHAIN

TABLE 2				
DASH NO	"A" DIA	"B" DIA	"C" DIM	"D" DIA
-02	.630	.750	1.065	.450
-03	.505	.625	.941	.369
-04	.439	.562	.878	.355
-05	.380	.500	.816	.325
-06	.317	.437	.753	.295
-07	.281	.408	.722	.278
-08	.610	.750	1.066	.450
-09	.567	.687	1.003	.419
-008	.330	.450	.796	.300


INCH	MM	INCH	MM	INCH	MM	INCH	MM	INCH	MM
.005	0.13	.200	7.37	.410	10.64	.625	15.88	.941	23.90
.010	0.25	.295	7.49	.437	11.10	.830	20.90	1.003	25.48
.030	0.76	.300	7.62	.436	11.15	.867	21.45	1.066	27.08
.032	0.81	.317	8.05	.450	11.43	.722	18.34	2.5	63.50
.062	1.57	.325	8.26	.500	12.70	.750	19.05	3.0	76.20
.140	3.55	.330	8.38	.505	12.83	.753	19.13	4.0	101.60
.200	5.08	.355	9.02	.56	14.22	.766	19.40	4.5	114.30
.25	6.35	.380	9.65	.562	14.27	.816	20.73	6.0	152.40
.278	7.06	.388	9.85	.567	14.40	.827	21.01	7.0	177.80
.281	7.14	.406	10.31	.610	15.48	.878	22.30	10.0	254.00




-1 SHOWN
NO CHAIN, STAINLESS STEEL ROPE OR MOUNTING LUG




-2-△ THRU -11-△ SHOWN
STANDARD CHAIN & BASIC MOUNTING LUG



-12-△ THRU
-17-△ SHOWN
STAINLESS STEEL ROPE AND BASIC MOUNTING LUG



-2-△ -02 THRU
-11-△ -008 SHOWN
STANDARD CHAIN AND BULKHEAD JACK MOUNTING LUG



-12-△ -02 THRU
-17-△ -008 SHOWN
STAINLESS STEEL ROPE AND BULKHEAD JACK MOUNTING LUG


△ NOTE LENGTH FOR SST ROPE WITH MTG LUG OPTION IS NOT MEASURED TO CENTER OF BULKHEAD MTG LUG

5. EXAMPLE OF COMPLETE MODEL NO:
TN1-1-02
BASIC MODEL NO TN1 (50 OHM)
UTN1 (75 OHM)
CHAIN/ROPE MATL AND LENGTH (SEE TABLE 1)
BULKHEAD JACK MOUNTING LUG (OPTIONAL) WITH BRASS OR NYLON CHAIN AND STAINLESS STEEL ROPE (SEE TABLE 2)

4. TERMINATED MALE COAXIAL 50 & 75 OHM N TYPE PLUG WITH CHAIN & MOUNTING LUG OPTIONS

△ RESISTANCE VALUE IN OHMS (1/2W, 1%) SHOWN SHORTED TO CASE AND RESISTOR

2. FINISH: TFS-1A (NICKEL)
1. ALL DIM ARE IN INCHES



QTY	DESCRIPTION	PART NUMBER	ITEM
10, UNLESS SPECIFIED			
BY ± .005			
WIDE			
ANGLES			
DWN 1 DKC 9-30-88	MATERIAL	CODE IDENT	DRAWING NO
CHK 6M 10-6-88	14949	105-0376	REV
ENGR 7/7			H
APPR 1/1	SCALE 2/1	DATE 11-27-72	SHEET 1C